

DEC 1 1947

DUPLICATE

## OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

HOBBS OFFICE

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	X		

November 28, 1947

Hobbs, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the \_\_\_\_\_

The Ohio Oil Company

A. C. Taylor "D"

Well No. 1 in the \_\_\_\_\_

Company or Operator

Lease

SE/4, NE/4

of Sec. 9

T. 17-S

R. 32-E

N. M. P. M.,

West Roberts

Field,

Lea

County.

The dates of this work were as follows: \_\_\_\_\_

Notice of intention to do the work was (~~submitted~~) submitted on Form C-102 on November 24, 1947and approval of the proposed plan was (~~obtained~~) obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Total depth 4026' White Dolomite. Well has been a banded and plugged according to the following procedure: 1380' of 5½" csg. was recovered. A 30 sax cement plug was set @ 4026' up to 3758', a 10 sax plug was set in top of 5½" csg. (which was left in hole @ 1380' and was set thru salt section @ 3840' and cemented W/500 sax) all intervals between plugs were filled with heavy mud laden fluid, sand and gravel used for bridging. 8-5/8" surface casing was set @ 1105' cemented W/300 sax cement and was left intact as this cement was circulated, the top 20' of this string was filled W/18 sax cement plug. 4½" marker was set in cement to extend 5' above surface.

Witnessed by J. B. Reese

The Ohio Oil Company

Foreman

Name

Company

Title

Subscribed and sworn before me this \_\_\_\_\_

I hereby swear or affirm that the information given above is true and correct.

28 day of November, 1947

Name P. B. StewartPosition SuperintendentRepresenting The Ohio Oil Company  
Company or OperatorAddress Box 1607, Hobbs, New MexicoNotary Public  
My Commission Expires August 19, 1951

My commission expires \_\_\_\_\_

Remarks:

APPROVED

Date DEC 1 1947

Rog Yarbrough  
Name  
OIL & GAS INSPECTOR  
Title