

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIP
(Other instructions
reverse side)Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

12-059576

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐		7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR Standard Oil Company of Texas, A Division of California Oil Company		8. FARM OR LEASE NAME Ties Federal	
3. ADDRESS OF OPERATOR 3610 Avenue B - Snyder, Texas		9. WELL NO. 29	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface Unit G, 1980' FWL and 1980' FWL, Section 10, T-17S, R-32E		10. FIELD AND POOL, OR WILDCAT No. 1 Junior (Gentryburg-San Andres)	
14. PERMIT NO.		15. ELEVATIONS (Show whether DF, RT, GR, etc.) GR 4153'	
11. SEC. T. R. S. OR BLM. AND SURVEY OR AREA Unit G, Section 10, T-17, R-32		12. COUNTY OR PARISH Lea	
13. STATE New Mexico			

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Moved in rotary rig, installed series 900 blowout preventor, spudded 4:00 P.M. 5-3-65.
2. Drilled 4-3/4" hole from existing total depth of 4180'-4160', cased from 4160' to total depth 4188'; ran logs, released rig at 12:00 midnight, 5-9-65.
3. Moved in pulling unit, displaced mud in hole with water, spotted 500 gals acetic acid, perforated 3942'-3965'.
4. Frased 4088'-4052' with 10,000 gals gelled water, sand and beads, frased 3894'-3905' with 30,000 gals gelled water, 13,000# sand, 3000# glass beads and 700# gyban with 1000# rocksalt in stages.
5. Pulled free tubing, packer and retrievable bridge plug, ran 2 1/2" production string, rods and pump and placed on production.

18. I hereby certify that the foregoing is true and correct

SIGNED

R. E. Rigby
R. E. Rigby

TITLE

Lead Drilling Engineer

DATE

June 2, 1965

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

J. L. GORDON
ACTING DISTRICT ENGINEER

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1987-O-883222

6-87-10-11