

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLY
(Other instructions
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

1A 039076

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Battus
Das Federal Report 3

9. WELL NO.

10. FIELD AND POOL, OR WILDCAT

Malheur
Crown Point, Oregon11. SEC., T., R., M., OR B.L. AND
SURVEY OR AREA

12-14-32

12. COUNTY OR PARISH

13. STATE

Las
New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug a well to a different reservoir.
Use "APPLICATION FOR PERMIT TO DRILL" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	2. NAME OF OPERATOR Standard Oil Company of Texas A Division of Chevron Oil Company	3. ADDRESS OF OPERATOR 3610 Avenue B - Bayard, Texas	4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface Unit A; 660' FWL and 660' FWL of Section 10 T-17-S, R-32-E	14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4205' RT
--	---	---	--	----------------	--

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐
REPAIR WELL ☐	CHANGE PLANS ☐
(Other) ☐	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREATMENT ☒	ALTERING CASING ☐
SHOOTING OR ACIDIZING ☒	ABANDONMENT* ☐
(Other) ☒ Supplementary Well History	
(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Moved in pulling unit, pulled rods and tubing, installed blow out preventer.

Ran 4-3/4" bit and cleaned out to 4205', pulled bit, ran gamma ray - neutron log. Perforated interval 4015-4043 with 4 C.J.T. Ran full bore retrievable cementer and set at 3500'; acidized with 2000 gals and acid.

Frased with 15,000 gals gelled water, 27,000 lbs sand and 750 lbs P-3 in 3 stages separated by rock salt and mothballs.

Ran 4-3/4" bit and cleaned out to 4205', pulled bit and ran production string, placed well on production.

18. I hereby certify that the foregoing is true and correct

SIGNED

B. Davidson

TITLE

Lead Drilling Engineer

DATE

October 21, 1965

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED

OCT 21 1965

*See Instructions on Reverse Side

J. L. GORDON
ACTING DISTRICT ENGINEER

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top for any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963—O-685229

997-611

NOV 5 11 24 AM '82