


4985  
CORRECTED

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD



Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPPLICATE. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.

AREA 640 ACRES  
LOCATE WELL CORRECTLY

J. C. Watson & R.T. Piner Box 536, Artesia, New Mexico

Trimble Company or Operator Address

Well No. 2 A in SE NE of Sec. 11, T. 17S

32E

R. N. M. P. M. West Hobbs Field, Lea County.

Well is 2010 feet south of the North line and 660 feet west of the East line of Sec. 11-17S-32E

If State land the oil and gas lease is No. Assignment No.

If patented land the owner is Mrs. W. E. Trimble Address Seminole, Texas

If Government land the permittee is Address

The Lessee is J. C. Watson & R. T. Piner Address Box 536, Artesia, N. M.

Drilling commenced February 19 46 Drilling was completed June 19 46

Name of drilling contractor J. C. Watson Drig. Co. Address Box 536, Artesia, N. M.

Elevation above sea level at top of casing feet.

The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from 4160 to 4174 No. 4, from to  
No. 2, from 4248 to 4259 No. 5, from to  
No. 3, from 4285 to 4295 No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 3535 to 3545 feet.  
No. 2, from to feet.  
No. 3, from to feet.  
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
8 5/8"	32#	8	S. E.	1232	Baker				
5 1/2"	14#	8	New	4062	Larkin				
7"				3511					

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
10"	8 5/8"	1232	50	Halliburton		
6"	5 1/2"	4062	50	Halliburton		

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set  
Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 1232 feet, and from feet to feet  
Cable tools were used from 1232 feet to 4295 feet, and from feet to feet

PRODUCTION

Put to producing May 27 19 46  
The production of the first 24 hours was 100 bbls. barrels of fluid of which 100 % was oil; % emulsion; % water; and % sediment. Gravity, Be.  
If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas.  
Rock pressure, lbs. per sq. in.

EMPLOYEES

John Mengwasser Driller H. E. Oliver Driller  
D. E. Selman Driller J. C. Watson Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 3rd day of July 19 46  
Notary Public  
My Commission expires Feb 23, 1947  
Artesia, New Mexico 7-3-46  
Name  
Position Office Manager  
Representing J. C. Watson & R. T. Piner Company or Operator  
Address Box 536, Artesia, New Mexico.

## FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	1232	1232	Drilled with Rotary tools and set 8 5/8" casing at 1232'. No data available on formation.
1232	1360	128	Anhydrite
1360	1465	105	Salt & Red Bed
1465	1795	330	Salt & Anhydrite
1795	2240	445	Salt
2240	2400	160	Salt & Potash
2400	2485	85	Anhydrite & Red Rock
2485	2580	95	Anhydrite
2580	2700	120	Red Bed & Anhydrite
2700	3305	605	Anhydrite
3305	3455	150	Anhydrite & Red Bed
3455	3525	70	Anhydrite
3525	3555	30	Red Sand - Show of Oil & Water at 3525-35.
3555	3715	160	Anhydrite
3715	3786	71	Red Rock & Anhydrite
3786	3992	206	Anhydrite
3992	4160	168	Lime
4160	4175	15	Sandy Lime - Oil Saturated.
4175	4194	19	Lime
4194	4199	5	Gray lime
4199	4201	2	Brown lime
4201	4253	52	Lime
4253	4259	6	Sandy Lime Increase in Gas
4259	4295	36	Lime
4295	Total	Depth	