Form 3160-5 (June 1990)

UNITED STATES DE

P.O. BOX 198

FORM APPROVED -0135 93

DEPARTMENT OF THE INTERIONOBBS, NEW MEXICO	88240	Budget Bureau No. 1004- Expires: March 31, 199
BUREAU OF LAND MANAGEMENT		Lease Designation and Serial

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

al No LC-061842 6. If Indian, Allottee or Tribe Name

Use "APPLICATION FO	R PERMIT—" for such proposals	
SUBMIT	IN TRIPLICATE	7. If Unit or CA, Agreement Designation
Type of Well		
Well Gas Other Inic	1 n +	8. Well Name and No.
Name of Operator		Miller BX #1
Mack Energy Corporation		9. API Well No.
Address and Telephone No.		30-025-00543
P.O. Box 960, Artesia, NM 88	3211-0960 (505)748-1288	10. Field and Pool, or Exploratory Area
Location of Well (Footage, Sec., T., R., M., or Survey D		Maljamar GRBG SA
660 FSL 660 FEL		11. County or Parish, State
Sec. 14-T17S-R32E		
		Lea, NM
CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REP	PORT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	N
XX Notice of Intent	Abandonment	Change of Plans
	Recompletion	New Construction
Subsequent Report	Plugging Back	Non-Routine Fracturing
	Casing Repair	Water Shut-Off
Final Abandonment Notice	Altering Casing	Conversion to Injection
	Other	Dispose Water
		(Note: Report results of multiple completion on Well Completion of Recompletion Report and Log form)

- 13 Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled. give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*
 - Circ hole w/mud laden fluid.
 - 2. Spot cmt plug from PBTD to 2600'.
 - Tag plug @ 2600'.
 - Spot 25sx plug 50' below base salt (2107').
 - Perf csg 50' below top salt (1193').
 - 6. Squeeze perfs w/25sx plug.
 - Tag plug @ 1093'. 7.
 - Perf csg 50' below 8 5/8" shoe.
 - Attempt to circ hole w/cmt from 200'.
 - Install dry hole marker and clean location.
 - We will need a workover pit on this location. 11.

Signed Carter	Title	Production Clark	Date 4-7-95
(This space for Federal or State office use)		_	
Approved by Orig. Signed by Adam Saiameh Conditions of approval, if any:	Title	Petroleum Engineer	Date 4/20/95
- SEE ATTACHED -			

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

Bog to the second of the seco

OFFICE

BUREAU OF LAND MANAGEMENT CARLSBAD RESOURCE AREA

Permanent Abandonment of Wells on Federal Lands

Conditions of Approval

- 1. Approval: Plugging operations shall commence within 98 days from the approval date of plugging procedure.
- 2. <u>Notification:</u> Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Eddy County call (505)887-6544; for wells in Lea County call (505) 393-3612.
- 3. <u>Blowout Preventers:</u> A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The minimum BOP requirement is a 2M system for a well not deeper than 9,696 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.
- 4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging and shall be obtained by mixing at the rate of 25 sacks (56 pounds each) of gel per 166 barrels of water. Minimum nine (9) pounds per gallon.
- 5. <u>Cement Requirement:</u> Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either class "C", for up to 7,500 feet of depth, mixed at 14.8 lbs./gal. with 6.3 gallons of fresh water per sack or class "H", for deeper than 7,500 feet plugs, mixed at 16.4 lbs./gal. with 4.3 gallons of fresh water per sack.

- 6. Dry Hole Marker: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The well bore shall then be capped with a 4-inch pipe, 18-feet in length, 4 feet above ground and embedded in cement. The following information shall be permanently inscribed on the dry hole marker: Well name and number, the name of the operator, the lease serial number, the surveyed location (the quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer; such as metes and bounds).
- 7. <u>Subsequent Plugging Reporting:</u> Within 36 days after plugging work is completed, file one original and five copies of the Subsequent Report of Abandonment, Form 3166-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. Show <u>date</u> well was plugged.

Following the submittal and approval of the Subsequent Report of Abandonment, surface restoration conditions of approval will be developed and furnished to you.