

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN DUPLICATE
(Other Instructions on Reverse Side)Form Approved
Budget Project 2-1-1

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ <i>water inj. well</i>	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR <i>Continental Oil Company</i>	8. FIRM OR LEASE NAME <i>millers B X</i>
3. ADDRESS OF OPERATOR <i>P. O. Box 460, Hobbs, New Mexico 88240</i>	9. WELL NO. (M.) <i>1</i>
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface <i>660' FSL & 660' FEL of sec 14, T-17S, R-32E, in Lea County, N. Mex.</i>	10. FIELD AND FOOT, OR WHOLE <i>sec 14, T-17S, R-32E</i>
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, CR, etc.) <i>4085' DF</i>
12. COUNTY OR PARISH <i>Lea</i>	13. STATE <i>N. M.</i>

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) *Converted to water inj.*

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of start of proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and points pertinent to this work.)

This well was converted to water inject by the following procedure.

Ran 4 3/4" bit and cleaned out from 4181' to 4265'. Perforated 5 1/2" casing with one (.45") IS from 4125' to 4131'. Treated perfs with 500 gal 15% mud acid followed with a 10,000 gal water 15,000 # sand frac. Ran 2 3/8" cement lined tubing with packer. Displaced annulus with treated water and set packer at 3960'.

Commenced injection on 9-25-69 and tested

injection at 500 BWPD with no pressure.

18. I hereby certify that the foregoing is true and correct

SIGNED

*M. E. [Signature]*TITLE *Adm. Section Chief*

DATE

3-18-

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

USGS-5

FILE

ACCEPTED FOR RECORD

MAR 19 1970

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

*See Instructions on Reverse Side