

UNITED STATES  
DEPARTMENT OF THE INTERIOR

SUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)

Form approved.  
Budget Bureau No. 42-R1024

GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR <i>Continental Oil Company</i>	8. FARM OR LEASE NAME <i>Miller BX</i>
3. ADDRESS OF OPERATOR <i>Box 460, Hobbs, N. Mex.</i>	9. WELL NO. <i>1</i>
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface <i>660' FSL + 660' FEL, of Sec. 14, T-17S, R-32E, in Lea County, N. Mex.</i>	10. FIELD AND POOL, OR WILDCAT <i>Maljano G-5A Repur</i>
14. PERMIT NO.	11. SEC., T., R., M., OR B.L. AND SURVEY OR AREA <i>Sec. 14, T-17S, R-32E</i>
15. ELEVATION (Show whether DF, RT, CR, etc.) <i>4085' DF</i>	12. COUNTY OR PARISH <i>Lea</i>
	13. STATE <i>N. Mex.</i>

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) *Convert to water inj.* ☒

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON\* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT\* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

*It is proposed to convert this well to water injection by the following procedures.*

*Clean out to 4250'. Run 2 3/8" OD cement-lined tubing with packer, and set packer at approx. 3975'. Place well on injection*

18. I hereby certify that the foregoing is true and correct

SIGNED

*M. E. Yeakley*

TITLE

*Adm. Section Chief*

DATE

*5-14-69*

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

**APPROVED**

MAY 15 1969

ARTHUR R. BROWN  
DISTRICT ENGINEER

\*See Instructions on Reverse Side