

LOG OF OIL OR GAS WELL

LOCATE WELL CORRECTLY

The information given herewith is a complete and correct record of the well and all work done thereon so far as can be determined from all available records.

Signed _____
Date 1-2-62 _____
Title District Superintendent

Commenced drilling 12-10, 1961 Finished drilling 12-15, 1961

OIL OR GAS SANDS OR ZONES
(Denote gas by G)

No. 1, from ~~1000~~ to ~~1335~~-----

No. 2, from ----- to -----

No. 3, from ----- to -----

No. 4, from ----- to -----

No. 5, from ----- to -----

No. 6, from ----- to -----

IMPORTANT WATER SANDS

No. 1, from _____ to _____

No. 2, from _____ to _____

No. 3, from _____ to _____

No. 4, from _____ to _____

CASING RECORD

[illegible]

MUDDING AND CEMENTING RECORD

Size casing	Where set	Number sacks of cement	Method used	Mud gravity	Amount of mud used
7 5/8	1040	450	Pump & Plug		
4 1/2	4000	200	Pump & Plug		

PLUGS AND ADAPTERS

USGS-4 NMCC-2 WAM File **PLUGS AND ADAPTERS**
 Heaving plug—Material _____ Length _____ Depth set _____
 Adapters—Material _____ Size _____

SHOOTING RECORD

Size	Shell used	Explosive used	Quantity	Date	Depth shot	Depth cleaned out

TOOLS USED

Rotary tools were used from 0 feet to 4335 feet, and from _____ feet to _____ feet.

Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet.

DATES

....., 19.....	Put to producing	12-37.....	19-61.....
----------------	------------------------	------------	------------

The production for the first 24 hours was 97 barrels of fluid of which 100% was oil; —% emulsion; —% water; and —% sediment. Gravity, °Bé. 36

If gas well, cu. ft. per 24 hours ----- Gallons gasoline per 1,000 cu. ft. of gas -----

Rock pressure, lbs. per sq. in.

EMPLOYEES (Blue Pacific Drilling Company)

C. B. Henderson	Driller	W. R. Benson	Driller
Chas. Jones	Driller	W. R. Benson	Driller

FORMATION RECORD

FROM—	TO—	TOTAL FEET	FORMATION
0	1111	1111	Red beds
1111	2192	1081	Salt
2192	2353	161	Anhyd, Sm. Shale
2353	2705	352	Sand, Shale, Anhyd. Sm. Dolo.
2705	3324	619	Dolo. & Anhyd, Sm. Shale & Sd.
3324	3764	440	Sand, Dolo. & Anhyd, Sm. Shale
3764	4016	252	Sand, Dolo. & Anhyd.
4016	4074	58	Sand
4074	4335	261	Dolomite, Sm. Sd.

Tops: Rustler 996, Salado 1111, Fansill 2192, Yates 2353, Seven Rivers 2705, Queen 3324, Grayburg 3764, 6th Zone 4016, San Andres 4074, 8th Zone 4273.

It is of the greatest importance to have a complete history of the well. Please state in detail the dates of redrilling, together with the reasons for the work and its results. If there were any changes made in the casing, state fully, and if any casing was "struck" or left in the well, give its size and location. If the well has been dynamited, give date, size, position, and number of shots. If plugs or bridges were put in to test for water, state kind of material used, position, and results of pumping or bailing.

Open hole formation notched with explosive jets at 4284', 4165', 4042'. Treated with 30,000 gallons lease crude, 35,000 sand, and 1,000 gallons admixte.

HISTORY OF OIL OR GAS WELL

16-43094-2 U. S. GOVERNMENT PRINTING OFFICE