

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPlicate
(Other instructions on reverse side)

Revised Bureau No. 100-5
Effective August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

LEASE DESIGNATION AND SERIAL NO.

hc-029405 B

IF INDIAN, ALLOTTEE OR TRIBE NAME

UNIT AGREEMENT NAME

MCA Unit

FARM OR LEASE NAME

MCA Unit

WELL NO.

No. 7

FIELD AND POOL, OR WILDCAT

Malheur 9-SA

SEC., T., R., M. OR BLK. AND SURVEY OR AREA

S. 17, T. 15, R. 32E

COUNTY OR PARISH

hca

STATE

nm

1. OIL WELL ☐ GAS WELL ☐ OTHER Injection

2. NAME OF OPERATOR

Conoco Inc.

3. ADDRESS OF OPERATOR

P.O. Box 460

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)

Unit h-f

1650' FWH / 1310' FWH

14. PERMIT NO.

30-025-0039800

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4032'

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

11/29/89 Notified BLM prior to RU.
Ran cement retainer + squeeze bottom perfs. Pick up 5 1/2 cement retainer, run in hole with 2-3 1/8 tbg, set at 3538'. head hole with mud. Squeeze 75 sks cement. SI pressure at 2100' psi. Pull out + spot 25 sk cement on top. Perf 4 shots @ 700' Brake circ. to surface between 5 1/2 + 8 5/8 with 225 sks. Rig down Rm equip. Erect perm. abandonment marker. Restore location.

RECEIVED

18. I hereby certify that the foregoing is true and correct

SIGNED W. B. Baker

TITLE Administrative Supervisor

DATE 1/25/90

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE Supervisor

DATE 4-7-90

*See Instructions on Reverse Side