

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

HOBBS OFFICE OCC
1956 APR 25 AM 8:58

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other) SANDFRAC	X

April 23, 1956

(Date)

Maljamar, New Mexico

(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Kewanee Oil Company

(Company or Operator)

State NO

(Lease)

Glover Drilling Company

(Contractor)

Well No. 3 in the SW $\frac{1}{4}$ NW $\frac{1}{4}$ of Sec. 16

T. 17S, R. 32E, NMPM., Maljamar Pool, Lea County.

The Dates of this work were as follows: March 21, 1956 to April 6, 1956

Notice of intention to do the work (was) filed submitted on Form C-102 on March 22, 19 56

(Cross out incorrect words)

and approval of the proposed plan (was) filed obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Moved in cable tools, pulled rods & 2" tubing, cleaned well out to 3991' and set calseal plug at 3903'. Ran 3" tubing in hole with Guiberson C-1 packer and set packer at 3532.07'. Dowell, Inc. sandfraced well with 20,000 gals. gelled lease crude and 30,000# sand on 4-3-56. Maximum treating pressure - 3500 psi. Injection rate - 19.65 barrels per minute. Total load and treating oil to recover - 868.00 bbls. Pulled 3" tubing with packer out of hole, ran 2" tubing and rods in hole and put well to pumping on 4-5-56. Recovered all load oil on 4-15-56. After load oil was recovered, well tested 50.00 barrels of oil and 43.19 MCF gas in 24 hours for a gas-oil ratio of 863.

Production before workover was 9 BOFD.

Witnessed by R. A. McGill

(Name)

Kewanee Oil Company

(Company)

District Superintendent

(Title)

Approved:

OIL CONSERVATION COMMISSION

[Signature]

(Name)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name [Signature]

Position District Superintendent

Representing KEWANEE OIL COMPANY

Address P. O. Box 124, Maljamar, New Mexico

(Title)

(Date)