NE. MEXICO OIL CONSERVATION COM. SSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications conserved by the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and

NOTICE OF INTENTION TO TEST CASING SHUT-OFF	notice by checking below: NOTICE OF INTENTION TO SHOOT OR	
OTICE OF INTENTION TO CHANGE PLANS	CHEMICALLY TREAT WELL NOTICE OF INTENTION TO PULL OR	
OTICE OF INTENTION TO REPAIR WELL	OTHERWISE ALTER CASING	
	Norman or with	
OTICE OF INTENTION TO DEEPEN WELL	NOTICE OF INTENTION TO PLUG WELL	XXX
	Odessa, Texas Novem	aber 4,
IL CONSERVATION COMMISSION, anta Fe, New Mexico		••
entlemen:		
ollowing is a notice of intention to do certain work a	as described below at the	
Company or Operator Les	B-3380 Well No. 2 in	SW/4
f Sec. 16 T. 17-S R. 32-E	, N. M. P. M., Maljamar	Field
Lea County.		
D. 4075. This well drilled to		
055. Shut well in 3 days and foumped gravel from 4075-4052 and	shot with 140 Quarts Solidified	hole. Nitro
055. Shut well in 3 days and foumped gravel from 4075-4052 and erin from 4000-4052. Cleaned ou	ound 3 bailers oil, no water in shot with 140 Quarts Solidified at to bottom after shot. Recove	hole. Nitro
055. Shut well in 3 days and foumped gravel from 4075-4052 and erin from 4000-4052. Cleaned ound bailed 8 gallons oil, no wate We therefore wish to cement wi	and 3 bailers oil, no water in shot with 140 Quarts Solidified at to bottom after shot. Recover, 8 hours. Hole dry th 25 sacks from 4075 - 4025 to	hole. Nitro ered oi
055. Shut well in 3 days and foumped gravel from 4075-4052 and erin from 4000-4052. Cleaned ound bailed 8 gallons oil, no wate We therefore wish to cement wince of oil herizon. Heavy mud from 3930-3875 to cover bottom of	and 3 bailers oil, no water in shot with 140 Quarts Solidified at to bottom after shot. Recover, 8 hours. Hole dry. th 25 sacks from 4075 - 4025 to rom 4025-3930. Cement with 20 oil string. Heavy mud from 38	hole. Nitro red oi cover sacks 375-209
oss. Shut well in 3 days and foumped gravel from 4075-4052 and erin from 4000-4052. Cleaned ou and bailed 8 gallons oil, no wate we therefore wish to cement wince of oil herizon. Heavy mud from 3930-3875 to cover bottom of ement with 10 sacks from 2090-20	and 3 bailers oil, no water in shot with 140 Quarts Solidified at to bottom after shot. Recover, 8 hours. Hole dry. th 25 sacks from 4075 - 4025 to rom 4025-3930. Cement with 20 oil string. Heavy mud from 38 to cover base of salt. Heavy	hole. Nitro red oi cover sacks 75-209 mud f
oss. Shut well in 3 days and formped gravel from 4075-4052 and erin from 4000-4052. Cleaned out the bailed 8 gallons oil, no wate we therefore wish to cement with acc of oil herizon. Heavy mud from 3930-3875 to cover bottom of ement with 10 sacks from 2090-20060 - 900. Cement with 35 sacks from 820 to bottom of cellar. Cement 820 to bottom of cellar.	and 3 bailers oil, no water in shot with 140 Quarts Solidified at to bottom after shot. Recover, 8 hours. Hole dry. th 25 sacks from 4075 - 4025 to rom 4025-3930. Cement with 20 coil string. Heavy mud from 38 from 900-820 on top of salt. Heavy ment with 10 sacks cement from	hole. Nitro red oi cover sacks 75-209 mud f Heavy
oss. Shut well in 3 days and formped gravel from 4075-4052 and erin from 4000-4052. Cleaned out the bailed 8 gallons oil, no wate we therefore wish to cement with acc of oil herizon. Heavy mud from 3930-3875 to cover bottom of ement with 10 sacks from 2090-20060 - 900. Cement with 35 sacks from 820 to bottom of cellar. Cement 820 to bottom of cellar.	and 3 bailers oil, no water in shot with 140 Quarts Solidified at to bottom after shot. Recover, 8 hours. Hole dry. th 25 sacks from 4075 - 4025 to rom 4025-3930. Cement with 20 coil string. Heavy mud from 38 from 900-820 on top of salt. Heavy ment with 10 sacks cement from	hole. Nitro red oi cover sacks 75-209 mud f Heavy
oss. Shut well in 3 days and formped gravel from 4075-4052 and erin from 4000-4052. Cleaned out the bailed 8 gallons oil, no wate we therefore wish to cement with acc of oil herizon. Heavy mud from 3930-3875 to cover bottom of ement with 10 sacks from 2090-20060 - 900. Cement with 35 sacks from 820 to bottom of cellar. Cement 820 to bottom of cellar.	and 3 bailers oil, no water in shot with 140 Quarts Solidified at to bottom after shot. Recover, 8 hours. Hole dry. th 25 sacks from 4075 - 4025 to rom 4025-3930. Cement with 20 coil string. Heavy mud from 38 from 900-820 on top of salt. Heavy ment with 10 sacks cement from	hole. Nitro red oi cover sacks 75-209 mud f Heavy
oss. Shut well in 3 days and formped gravel from 4075-4052 and erin from 4000-4052. Cleaned ound bailed 8 gallons oil, no wate we therefore wish to cement with acc of oil herizon. Heavy mud from 3930-3875 to cover bottom of ement with 10 sacks from 2090-20060 - 900. Cement with 35 sacks from 820 to bottom of cellar. Cement with 35 sacks from 820 to bottom of cellar.	and 3 bailers oil, no water in shot with 140 Quarts Solidified at to bottom after shot. Recover, 8 hours. Hole dry. th 25 sacks from 4075 - 4025 to rom 4025-3930. Cement with 20 coil string. Heavy mud from 38 from 900-820 on top of salt. Heavy ment with 10 sacks cement from	hole. Nitro red oi cover sacks 75-209 mud f Heavy
oss. Shut well in 3 days and foumped gravel from 4075-4052 and erin from 4000-4052. Cleaned ound bailed 8 gallons oil, no wate We therefore wish to cement winge of oil herizon. Heavy mud from 3930-3875 to cover bottom of ement with 10 sacks from 2090-20060 - 900. Cement with 35 sacks rom 820 to bottom of cellar. Cellar to surface and set pipe ma	and 3 bailers oil, no water in shot with 140 Quarts Solidified at to bottom after shot. Recover, 8 hours. Hole dry. th 25 sacks from 4075 - 4025 to rom 4025-3930. Cement with 20 coil string. Heavy mud from 38 from 900-820 on top of salt. Heavy ment with 10 sacks cement from	hole. Nitro red oi cover sacks 75-209 mud f Heavy bottom
S55. Shut well in 3 days and formped gravel from 4075-4052 and prin from 4000-4052. Cleaned out the bailed 8 gallons oil, no water we therefore wish to cement with acc of oil herizon. Heavy mud from 3930-3875 to cover bottom of ement with 10 sacks from 2090-20 accept with 35 sacks from 820 to bottom of cellar. Capital to surface and set pipe materials and set pipe materials.	and 3 bailers oil, no water in shot with 140 Quarts Solidified at to bottom after shot. Recover, 8 hours. Hole dry. th 25 sacks from 4075 - 4025 to rom 4025-3930. Cement with 20 oil string. Heavy mud from 38 from 900-820 on top of salt. Heavy from 900-820 on top of salt. Ement with 10 sacks cement from refer.	hole. Nitro red oi cover sacks 75-209 mud f Heavy bottom
S55. Shut well in 3 days and formped gravel from 4075-4052 and prin from 4000-4052. Cleaned out the bailed 8 gallons oil, no water we therefore wish to cement with acc of oil herizon. Heavy mud from 3930-3875 to cover bottom of ement with 10 sacks from 2090-20060 - 900. Cement with 35 sacks from 820 to bottom of cellar. Cellar to surface and set pipe materials and set pipe materials.	and 3 bailers oil, no water in shot with 140 Quarts Solidified at to bottom after shot. Recover, 8 hours. Hole dry. th 25 sacks from 4075 - 4025 to rom 4025-3930. Cement with 20 oil string. Heavy mud from 38 from 900-820 on top of salt. Heavy from 900-820 on top of salt. Ement with 10 sacks cement from refer.	hole. Nitro red oi cover sacks 75-209 mud f Heavy bottom
NOV 18 19-	pund 3 bailers oil, no water in shot with 140 Quarts Solidified at to bottom after shot. Recovery, 8 hours. Hole dry. The 25 sacks from 4075 - 4025 to come 4025-3930. Cement with 20 coil string. Heavy mud from 38 from 900-820 on top of salt. Heavy from 900-820 on top of salt. Meant with 10 sacks cement from there. Phillips Petroleum Companion of Salt. Phillips Petroleum Companion of Salt. Phillips Petroleum Companion of Salt.	hole. Nitro red oi cover sacks 75-209 mud f Heavy bottom
oss. Shut well in 3 days and foumped gravel from 4075-4052 and erin from 4000-4052. Cleaned ou had bailed 8 gallons oil, no wate We therefore wish to cement wince of oil herizon. Heavy mud from 3930-3875 to ever bottom of ement with 10 sacks from 2090-20060 - 900. Coment with 35 sacks rom \$20 to bottom of cellar. Cestlar to surface and set pipe ma	pund 3 bailers oil, no water in shot with 140 Quarts Solidified at to bottom after shot. Recovery, 8 hours. Hole dry. The 25 sacks from 4075 - 4025 to come 4025-3930. Cement with 20 coil string. Heavy mud from 38 from 900-820 on top of salt. Heavy from 900-820 on top of salt. Meavy from 900-820 on top of salt. The sacks cement from arker. Phillips Petroleum Company of Operator Company Operator Company of Operator Company Operator Compa	hole. Nitro red oi cover sacks 75-209 mud f Heavy bottom
oss. Shut well in 3 days and foumped gravel from 4075-4052 and erin from 4000-4052. Cleaned ound bailed 8 gallons oil, no wate We therefore wish to cement wince of eil herizon. Heavy mud from 3930-3875 to cover bottom of ement with 10 sacks from 2090-20060 - 900. Cement with 35 sacks rom 320 to bottom of cellar. Cellar to surface and set pipe ma	pund 3 bailers oil, no water in shot with 140 Quarts Solidified at to bottom after shot. Recovery, 8 hours. Hole dry. The 25 sacks from 4075 - 4025 to come 4025-3930. Cement with 20 coil string. Heavy mud from 38 coil string. Heavy mud from 38 from 900-820 on top of salt. Heavy from 900-820 on top of salt. Heavy must be said to sacks cement from the reserved. Phillips Petroleum Companier. Phillips Petroleum Companier. Phillips Petroleum Companier. Position District Superinter.	hole. Nitro red oi cover sacks 75-209 mud f Heavy bottom
oss. Shut well in 3 days and foumped gravel from 4075-4052 and erin from 4000-4052. Cleaned ound bailed 8 gallons oil, no wate We therefore wish to cement wiace of oil herizon. Heavy mud from 3930-3875 to cover bottom of ement with 10 sacks from 2090-20060 - 900. Cement with 35 sacks rom 320 to bottom of cellar. Cellar to surface and set pipe ma	pund 3 bailers oil, no water in shot with 140 Quarts Solidified at to bottom after shot. Recovering to bottom after shot. Recovering the sacks from 4075 - 4025 to come 4025-3930. Cement with 20 coil string. Heavy mud from 38 from 900-820 on top of salt. Heavy from 900-820 on top of salt. Meavy from 900-820 on top of salt. Meavy from 900-820 on top of salt. Phillips Petroleum Companion with 10 sacks cement from the sacks cement from the sacks cement from the sacks. Position District Superinter Send communications regarding well to sacks cement grant to send communications regarding well to sacks cement from the sacks cement from	hole. Nitro red oi cover sacks 75-209 mud f Heavy bottom