

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
P.O. BOX 1530
HOBBS, NEW MEXICO 88240

Budget Bureau No. 1004--0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO.

LC-029405B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

MCA Unit

8. FARM OR LEASE NAME

MCA Unit Bty 1

9. WELL NO.

16

10. FIELD AND POOL, OR WILDCAT

Bash Maljamar-Balsal

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

17-17S-32E

12. COUNTY OR PARISH

13. STATE

Lea NM

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR
Conoco Inc.

3. ADDRESS OF OPERATOR
P.O. Box 460 - Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

660' FSL & 660' FWL - Unit Letter M

14. PERMIT NO.

30-025-00585

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting and proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Set retainer at 3576' & pump 375 sxs of class "C" cement.
Left 25 sxs on top of retainer. Ref squeeze holes at 1910' & 725'. Squeeze perfs at 1910' w/ 150 sxs class "C" cement.
Set retainer at 690' and squeeze perfs at 725' w/ 125 sxs of class "C" cement. Left 25 sxs cement on top of retained Ref at 450'. Shot 495' cement plug w/ class "C" cement.
Pump 1 sxs of cement in Bradenhead. Install P&A marker on 3/10/88

18. I hereby certify that the foregoing is true and correct

SIGNED *DF Finney* DF FINNEY

TITLE Administrative Supervisor

DATE April 20, 1988

(This space for signature or State office use)

APPROVED BY *[Signature]*
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE 5-24-88

Approved by
Liability under bond
See instructions on Reverse Side

*See instructions on Reverse Side

Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

BLM-Carlsbad(6) Cities(1) FPCO(1) File