

X		

(SUBMIT IN TRIPLICATE)
HOBBS OFFICE 000
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
7:23

Land Office **Las Cruces**
Lease No. **029405-B**
Unit **D**

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Wm. Mitchell "B"

Artesia, N. M. March 21, 1956

Well No. **26** is located **660** ft. from **[N]** line and **660** ft. from **[E]** line of sec. **17**

NM/A NW/4 Sec. 17 **17S** **32E** **NMPM**
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Maljamar
(Field)

Las
(County or Subdivision)

New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is _____ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

We propose to drill this well with rotary tools to a depth of about 4100'. 5 1/2" OD casing will be set at near total depth and cemented with 600 sacks of 8% Gel Incor cement followed by 100 sacks of 2% Gel Incor cement, which will be sufficient to bring cement above the top of salt. Casing will be perforated opposite pays and treated with sand-oil.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **BUFFALO OIL COMPANY**

Address **203 CARPER BUILDING**

ARTESIA, NEW MEXICO

By

Title

Dist. Supt.