UNITED STATES

JOHN AND WE C'

UNITED STATES	5. LEASE 5 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
DEPARTMENT OF THE INTERIOR	LC-029405 (6)
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
(Do not use this form for proposals to drill or to deepen or plus bank to a different	
reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas other	WE Mitchell B
	9. WELL NO. 1995 1 123
2. NAME OF OPERATOR	9 22 7 3 4
Conoco Inc. 3. ADDRESS OF OPERATOR	10. FIELD OR WILDCAT NAME
P.O. BOX 460, Hobbs, N.M.	Maljanar - 65A
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	11. SEČ., T., R., M., OR BLK. AND SURVEY OR AREA
below.)	Sec. 17, T-175, R-32E
AT SURFACE: 660'FSL & 1980'FEL AT TOP PROD. INTERVAL: Some	12. COUNTY OR PARISH 13. STATE
AT TOTAL DEPTH:	Lea N.M.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE.	14. API NO.
REPORT, OR OTHER DATA	
	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	
FRACTURE TREAT	
SHOOT OR ACIDIZE	
REPAIR WELL	(NOTE: Report results of multiple completion
PULL OR ALTER CASING	change on Form 9–330.)
CHANGE ZONES	SURVE.
ABANDON*	SICAMEXICO
(other) S. GEOLE,	ven i safaê şûşûşûşû û .
including estimated date of starting any proposed work. If well is dir measured and true vertical depths for all markers and zones pertinent	to this work.)*
MIRU A KITI WEN IF THECESSARY. 1884 WI	or oduction leavipment
MIRU & till well if necessary. POOH w) g Tag for fill & c/o w) jets up to 4170' of fill is	abore 4160 Pressure test
CSg. If recessary, squeeze of perfs., spott	ing 3 sx cut from 4110'-408's
CSg. If recessary, squeeze of pends, spott Squeeze w/ 50-100 sx. Class "C" cmt. D 40 gal. 15% HCI-NE acid from 4060'-40 4 TSPF. Prp. 2700 gal. 15% HCI-N Plush & saab. 614 w/ production equipment	vill out ent to 4150 Spot w/
40 gal. 15% HCI-NE word from 4060' - 41	095! Perf 4077' - 4088' W/
4 ISPF. Frp. 2700 gal. 15%, HC1-1	NE-FE dourhole.
Plush & swab. 614 W/ production equipment	+ & test well.
, , , , , , , , , , , , , , , , , , , ,	
Subsurface Safety Valve: Manu. and Type	Set @Ft.
18. I hereby certify that the foregoing is true and correct	
7/17/	7 2 2 2 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3
SIGNED WAY A Bullerfall TITLE Homin. Supervis	or 00/10/19
(This space for Federal or State offic	e usa VED a la l
APPROVED BYTITLE	
CONDITIONS OF APPROVAL, IF ANY:	T15 1919
1565 - 5 FILE	115 6 (2) (2) (3)
1 00	The same of the sa
•See Instructions on Reverse-Si	THE TRICT ENGINEERS
See instructions on Reverse Si	DISTRICT ENGINEERS STORES