Form 3160-5 June 1990)	DEPARTMEN	TED STATES T OF THE INTERIOR LAND MANAGEMENT	FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993 5 Lease Designation and Serial No.		
Do not u	SUNDRY NOTICES se this form for proposals to dri Use "APPLICATION FOR	6 If Indian, Allottee or Tribe Name			
- <u></u> -	SUBMIT	7. If Unit or CA, Agreement Designation			
Type of We Oil Weil Name of Of Cono Address and	Gas Sother Injectio	8. Well Name and Nogly 2 MCA Unit No. 42 9 API Well No. 3002500602 60			
4 Location of 1650 Sec.	Pesta Dr. Ste 100W, Midla Well (Footage, Sec., T., R., M., or Survey Dr FNL & 330' FEL 21, T-17S, R-32E CHECK APPROPRIATE BOX(10. Field and Pool. or Exploratory Area Maljamar Grayburg SA 11. County or Parish. State Lea RT. OR OTHER DATA			
	Subsequent Report	Abandonment Recompletion Plugging Back Casing Repair Altering Casing	Change of Plans New Construction Non-Routine Fracturing Water Shut-Off Conversion to Injection		
13. Describe P give s	Proposed or Completed Operations (Clearly state a subsurface locations and measured and true vertii	Dother <u>Casing Integrity Test</u> Il pertinent details, and give pertinent dates, including estimated date of starting cal depths for all markers and zones pertinent to this work.)*	Completion or Recompletion Report and Log form (
It is for te	proposed to perform the emporary abandonment:	following operations in order to prep	are this injection well		

1.	Notify BLM 24 hrs. prior t	to	performing	casing	integrity	test
2.	Pressure test the casing a	a t	500 ps1 to	r 30 mii	nutes.	
3.	Fill casing with packer fl	lui	id.			



14. L hereby centry that the foregoing is true and forrect Signed	Title	Sr. Conservation Coordinator	Date _	4/21/93
(This spece for Federal or State office use) Approved by	Tide _	LETROLEUM ENGINEER	Date _	5/13/93
See attached Title 18 U.S.C. Section 1001, makes it a crime for any person knowing or representations as to any matter within its jurisdiction.	iy and wilfi	ally to make to any department or agency of the United States	any faise.	, fictutious or fraudulent statement

MINIMUM REQUIREMENTS FOR CASING INTEGRITY TESTING OF WELLS ON FEDERAL LEASES IN THE CARLSBAD RESOURCE AREA

- 1. Contact the appropriate BLM office at least 24 hours prior to the scheduled test.
- NOTE: A BLM tecnician must be present to witness all casing integrity tests.
- 2. A retrievable bridge plug or packer shall be set a maximum of fifty (50) feet above any open perforations.
- 3. All downhole production equipment (tubing, rods, etc.) must be removed from the casing if they are not isolated by a packer.
- 4. The casing must be filled with fluid and pressure tested to 500 PSI. Further, the casing must be capable of holding this pressure for at least 30 minutes with a 10% allowable leak-off (ie., down to 450 PSI).
- 5. Wells that successfully pass the casing integrity test will be approved for Temporary Abandonment status for a period of 12 months provided that the operator submits a subsequent Sundry Notice requesting TA approval, and attaches a copy of The pressure test chart for the tested well.