

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE\*  
(Other instructions on reverse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-029509(a)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)1. ☐ OIL WELL ☐ GAS WELL ☐ OTHER WATER INJECTION WELL2. NAME OF OPERATOR  
CONTINENTAL OIL COMPANY3. ADDRESS OF OPERATOR  
Box 460, Hobbs, N.M. 882404. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface1650' FNL & 330' FEL OF SEC. 21

7. UNIT AGREEMENT NAME

MCA

8. FARM OR LEASE NAME

MCA UNIT

9. WELL NO.

42

10. FIELD AND POOL, OR WILDCAT

MAJ. G-SA REPRESS.11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREASEC. 21, T-17S, R-32E

12. COUNTY OR PARISH 13. STATE

LEAN.M.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4015' DF

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Pulled downhole eqpt. & tagged fill @ 3702'. Plugged back open hole w/ pea gravel to 3702'. Set 4 1/2" 9.5# k-55 Cond. "A" ST&C csq @ 3700'. Cemented w/ 300 sks. Class "C" cement. Plug down 11-16-74. TOC @ 700'. Tested w/ 1000#, held OK. Cleaned out to 3880'. Treated open hole w/ 2500 gal's 28% acid in two equal stages. Cleaned out sand to 4085'. Placed well back on injection. Work started 11-4-74, completed 11-21-74.

18. I hereby certify that the foregoing is true and correct

SIGNED

[Signature]

TITLE

SR. ANALYST

DATE

12-10-74

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD

DEC 12 1974

U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

\*See Instructions on Reverse Side

USGS-F, MCA-3, File