

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN
(Other instructions
reverse side)

DATE
on re-

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-029509(a)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

MCA

8. FARM OR LEASE NAME

MCA UNIT

9. WELL NO.

42

10. FIELD AND POOL, OR WILDCAT

Mali G-SA Repress.

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 21, T-17S R-32E

12. COUNTY OR PARISH

LEA

N.M.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ WATER INJECTION WELL

2. NAME OF OPERATOR
CONTINENTAL OIL COMPANY

3. ADDRESS OF OPERATOR
Box 460, Hobbs, N.M. 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1650' FNL E 330' FEL of Sec. 21

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RL, GR, etc.)

4015' DF

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

It is proposed to improve injection efficiency by the following means.
Run csq. inspection log. Set OH BP @ 3875'-3885'. Set OH pkr. @ 3820'.
Treat w/1500 gals 28% HCL-NE acid. If 7" csq. is in poor condition, run
4 1/2" 9.5# K-55 csq. from stc. to 3700'. Cement w/300 sks. Class "C" cmt.
If 7" csq. is in good condition, run 200' of 4 1/2" 9.5# K-55 csq
in cmt w/30 sks. Class "C" cmt. Squeeze if necessary w/25 sks Class "C"
cmt. Drill out & clean out to 4085'.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Sr. ANALYST

7-16-74

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED

JUL 17 1974 DATE

ARTHUR R. BROWN
DISTRICT ENGINEER

*See Instructions on Reverse Side

11565-5 MCA Partner (3), File