

Form 5-331
(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN DUPLICATE
(Other instructions on reverse side)

Form approved
Project Number No. 42-1111

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals.)

1. ☐ OIL WELL ☐ GAS WELL ☐ OTHER <u>WATER INJECTION WELL</u>	7. UNIT AGREEMENT NAME <u>MCA</u>
2. NAME OF OPERATOR <u>Continental Oil Company</u>	8. NAME OF LEASE NAME <u>MCA UNIT</u>
3. ADDRESS OF OPERATOR <u>P. O. Box 460, Hobbs, New Mexico 88240</u>	9. WELL NO. <u>42</u>
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) <u>At surface</u>	10. FIELD AND FOOT, OR WILDCAT <u>MALJ. G-SA REDRESS</u>
11. SEC., T., R., M., CORNER AND SURVEY OR AREA <u>1150' FNL 330' FEL SEC 21</u>	12. COUNTY OR PARISH <u>LEA</u>
13. ELEVATIONS (Show whether TP, RT, CR, etc.) <u>4015' DF</u>	13. STATE <u>N.M.</u>

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACURE TREATMENT

SHOOTING OR ACIDIZING

(Other) PLUG BACK IN SAME ZONE

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting and proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

SPOTTED 25 SXS CLASS "C" CEMENT W/3" SALT, 5" SAND + 1/4" FLO CELG PER SX AT 4107'. PULLED TUBING TO 4085' AND REVERSED OUT 15 SX TAGGED CEMENT @ 4098'. SPOTTED 12 SXS 10-20 SAND @ 4098'. TAGGED TOP OF SAND @ 4058'. SPOTTED 6 SXS 20-40 SAND AT 4037'. TAGGED SAND @ 4073'. SPOTTED 11 SXS 10-20 SAND AT 4027'. TAGGED TOP OF SAND AT 4028'. RAN 6 5/8" BAKER MODEL AD-I TENSION RICKER WITH 2 3/8" EUE, H-40, CEMENT LINED TUBING. SET AT 3991'. PLACED WELL BACK ON INJECTION.

18. I hereby certify that the foregoing is true and correct

SIGNED

M.C. Jordan

TITLE

Adm. Section Chief

DATE

6-23-70

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

JUN 24 1970

DATE

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

USGS-5

FILE

*See Instructions on Reverse Side

MCA PARTNERS