

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE  
(Other instructions  
reverse side)

Form approved.  
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. UNIT AGREEMENT NAME MCA	
2. NAME OF OPERATOR Continental Oil Company		8. FARM OR LEASE NAME MCA UNIT	
3. ADDRESS OF OPERATOR P.O. Box 460, Hobbs, New Mexico		9. WELL NO. 70	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980' FSL & 1980' FEL of Sec. 21-17S-32E, Lea County, New Mexico, NMPM		10. FIELD AND POOL, OR WILDCAT Maljamar Field Malj-Grbg-San Andres	
14. PERMIT NO.		15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4044' GL	
		12. COUNTY OR PARISH Lea	
		13. STATE N.M.	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
(Other) ☐

PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
ABANDON\* ☐  
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐  
FRACTURE TREATMENT ☐  
SHOOTING OR ACIDIZING ☐  
(Other) ☐

REPAIRING WELL ☒  
ALTERING CASING ☐  
ABANDONMENT\* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Communications in the MCA Unit Well No. 70 was eliminated using the following procedure:

- 1) Perforated two holes @ 2370' & ran packer to 2170.
- 2) Squeezed perfs W/150 sx Class "C" cement W/4% gel and 15# salt/sack, and 50 sack Class "C" neat W/3% HA-5. Top of cement @ 1750'.
- 3) Drilled out cement & plug to 4086'.

After workover - TD 4144', PB Depth 4086'. Well pumped 15 barrels of 37 degree gravity oil, 5 barrels of water, in 24 hours with 17 MCFGPD, CP 400 lbs., TP 50 lbs., with GOR of 1133.

Workover started 9-24-64, completed 9-28-64. Tested 9-30-64.

18. I hereby certify that the foregoing is true and correct

SIGNED \_\_\_\_\_

TITLE Staff Supervisor

DATE 10-14-64

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

TITLE \_\_\_\_\_

DATE \_\_\_\_\_

\*See Instructions on Reverse Side