

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPlicate
(Other instructions on
reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-029509(A)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

3. ADDRESS OF OPERATOR

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1-28-77 POOH w/ prod. equipment. WITH W/5 7/16" + 6 1/4" swages
in tandem; worked through tight spot in csq.
1-30-77 WITH w/bit. Jetted + CO fill from 3750'-3995'.
2-1-77 WITH w/5 1/4" Lynes OHBP. Set at 3695'
2-3-77 Ran + set 58 jts 4 1/2" casing at 3688' w/ 200 Sx.
Class "C" Cmt., 3#/sx salt, 1/4#/sx flocele, 2% CaCl₂,
40% CFR-2 + 150 Sx Class "C" Cmt., 3#/sx salt, 2% CaCl₂.
Displaced cmt. w/59 bbls. water.
2-4-77 Cut off csq. at csq. head.
2-5-77 Drill out float collar at 3634' + float shoe at
3676'. Drilled out cmt. + push OHBP to 3995'. MA set
at 3723', Sx at 3693'.
Install pumping equipment.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE ADMIN. SUPV.

DATE 5-26-77

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD

DATE

MAY 21 1977

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

*See Instructions on Reverse Side

USGS(5) MCA(4) 7:10