

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE*
(Other instructions reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-029509(a)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ <i>Water Injection</i>	7. UNIT AGREEMENT NAME <i>MCA</i>
2. NAME OF OPERATOR <i>Continental Oil Company</i>	8. FARM OR LEASE NAME <i>MCA Unit</i>
3. ADDRESS OF OPERATOR <i>P. O. Box 460, Hobbs, NM 88240</i>	9. WELL NO. <i>26</i>
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) <i>At surface</i> <i>660' FNL and 660' FWL of Sec 21</i>	10. FIELD AND POOL, OR WILDCAT <i>Maly G SA Repress</i>
14. PERMIT NO.	11. SEC. (T., R., M., OR BLK. AND SURVEY OR AREA) <i>Sec 21, T-17S, R-32E</i>
15. ELEVATIONS (Show whether DF, RT, GR, etc.) <i>4054' df</i>	12. COUNTY OR PARISH <i>Lea</i>
	13. STATE <i>NM</i>

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐

(Other)

PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☒

(Other)

REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled new 6 1/4" hole from 4145'-4175'. Treated OH 3905'-4175' w/2000 gals 28% acid. Set 4 1/2" 9.5# Casing @ 3734'. Cemented w/275 sacks class C cement. Drilled plug and cement to 3738' and tested casing w/1800 psi for 15 minutes, held O.K.

Completed - 4-26-73

18. I hereby certify that the foregoing is true and correct

SIGNED *Dug Bryn*TITLE *Sr. Analyst*DATE *5-29-73*

(This space for Federal or State office use)

APPROVED BY _____

TITLE _____

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

JUN 1 1973

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

*See Instructions on Reverse Side

USGS-5 FILE

MCA-3