Form 9-331 Dec. 1973

Form Approved. Budget Bureau No. 42-R1424

UNITED STATES

DEPARTMENT OF THE INTERIOR	
	2C-029509 (a)
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different	7. UNIT AGREEMENT NAME
reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas uvell other	9. WELL NO.
2. NAME OF OPERATOR NENTAL OIL COMPANY	7 10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR 460, Hobbs, N.M. 88240	Baish Yates 11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA
below.)	Sec 2/ T/75 R 32E
AT SURFACE: 23/0 FSL + 330 FEL AT TOP PROD. INTERVAL: ~	12. COUNTY OR PARISH 13. STATE
AT TOTAL DEPTH:	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
PEOLISCE FOR ARRESONAL TO: CHECKOUGHT REPORT OF	-1033'DF
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF	
FRACTURE TREAT	
SHOOT OR ACIDIZE	W F IN
SHOOT OR ACIDIZE REPAIR WELL BUILL OR ALTER CASING	Report results of multiple completion or zone change on Form 9–330.)
MULTIPLE COMPLETE	
CHANGE ZONES	
ABANDON* U. S. GEOLOGIC	AL SURVEY
(other) HOBBS, NEW	MEXICO
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine Subject well was PrA'd as follows	directionally drilled, give subsurface locations and nt to this work.)*
	•
1-18-73 MIRU	•
1-18-73 MIRU 1-19-73 set cont rete @ 2310'.	pmpd in 100 sks class "C
1-18-73 MIRU 1-19-73 Set cont rete @ 2310'. cont w/ 3 to salt per sk (0	pmpd in 100 sics class "C H 2351-2570'). Spo Hed 25
1-18-73 MIRU 1-19-73 set cont rete @ 2310'. cont w/ 3 to Dalt per sk (0 sks cont pluz From 900:8	pmpd in 100 sics class c H 2351-2370'). Spo Hed 25 Od' spotted 10 sk emt plug
1-18-73 MIRU 1-19-73 Set cont rete @ 2310'. cont w/ 3 to salt per sk (0	pmpd in 100 sics class c H 2351-2370'). Spo Hed 25 Od' spotted 10 sk emt plug
1-18-73 MIRU 1-19-73 set cont rete @ 2310'. cont w/ 3 to Dalt per sk (0 sks cont p/uz From 900:8	pmpd in 100 sics class c H 2351-2370'). Spo Hed 25 Od' spotted 10 sk emt plug
1-18-73 MIRU 1-19-73 set cont rete @ 2310'. cont w/ 3 to Dalt per sk (0 sks cont plug From 900:8	pmpd in 100 sics class c H 2351-2370'). Spo Hed 25 Od' spotted 10 sk emt plug
1-18-73 MIRU 1-19-73 Set cont rete @ 2310'. cont w/ 3 th salt per sk (0 sks cont plus From 900: 8 et surface . Well P+A as Subsurface Safety Valve: Manu. and Type	pmpd in 100 sics class "C H 2351-2570'). Spo Hed 25 Od' spotted 10 sk emt plug of 1-19=13
1-18-73 MIRU 1-19-73 Set cont rate @ 23/0'. cont w/ 3 to Dalt per sk (0 sks cont p/ug From 900: 8 at surface . Well P+A as Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct	pmpd in 100 sics class "C H 2351-2570'). Spo Hed 25 Od' spotfed 10 sk emt plug of 1-19=13 Set @Ft
1-18-73 MIRU 1-19-73 Let cont rete @ 2310'. Cont w/ 3 do Dalt per sk (0 sks cont plu; From 900: 8 at surface. Well P+A as Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct SIGNED The A. Mutterfield. TITLE Colministrate	pmpd in 100 sics class "C H 2351-2370'). Spo Hed 25 Od' spotted 10 sk emt plug of 1-19=13 Set @F
1-18-73 MIRU 1-19-73 Set cont rate @ 23/0'. cont w/ 3 to Dalt per sk (0 sks cont p/ug From 900: 8 at surface . Well P+A as Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct	pmpd in 100 sics class c H 2351-2370'). Spo Hed 25 00' spotted 10 sk emt plug of 1-19=13 Set @Ft
1-18-73 MIRU 1-19-73 Let cont rete @ 23/0'. cont w/ 3 delt per sk (0 sks cont plus from 900: 8 et surface. Well P+A as Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct SIGNED THE Administration (This space for Federal or States) APPROVED BY	pmpd in 100 sics class "C H 2351-2970'). Spo Hed 25 Od' spotted 10 sk emt plug of 1-19=13 Set @Ft
1-18-73 MIRU 1-19-73 Set ant rete @ 23/0'. Cmt w/ 3 Dalt per sk (0 sks cm+ p/u; From 900: 8 at surface . Wall P+A as Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct SIGNED THE Administration (This space for Federal or States)	pmpd in 100 sics class "C H 2351-2570'). Spo Hed 25 Od' spotfed 10 sk emt plug of 1-19=13 Set @Ft
1-18-73 MIRU 1-19-73 Let cont rete @ 23/0'. cont w/ 3 delt per sk (0 sks cont plus from 900: 8 et surface. Well P+A as Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct SIGNED THE Administration (This space for Federal or States) APPROVED BY	pmpd in 100 sics class "C H 2351-2570'). Spo Hed 25 Od' spotfed 10 sk emt plug of 1-19=13 Set @Ft
1-18-73 MIRU 1-19-73 Set cont rate @ 23/0'. cont w/ 3 ** Dalt per sk (0 sks cont p/u; From 900: 8 at surface. Wall P+A as Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct SIGNED WM A. Dutter TITLE Administration (This space for Federal or States of APPROVED BY	pmpd in 100 sics class "C H 2351-2970'). Spo Hed 25 Od' spotted 10 sk emt plug of 1-19=13 Set @Ft