

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on
reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-029509(b)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ WATER INJECTION
2. NAME OF OPERATOR Continental Oil Company
3. ADDRESS OF OPERATOR Box 460, Hobbs, N.M. 88240
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

7. UNIT AGREEMENT NAME

MCA

8. FARM OR LEASE NAME

MCA Unit

9. WELL NO.

36

10. FIELD AND POOL, OR WILDCAT

MALJ. G-SA Repress

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec 22 T-17S R-32E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4007' DF

12. COUNTY OR PARISH

Lea

13. STATE

N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

6-22-76 Ran 3 7/8" bit, DC's + Tbg. to bottom

6-23-76 Cleanout from 3403' to 3853'

6-24-76 " " 3853' to 3960'. Filled hole

w/10# brine. post w/ work string. Dumped 250
gallon pea gravel.6-25-76 - Dumped total 1570 gal. pea gravel to
6-26 fill open hole.

6-27-76 425 gallons pea gravel. Filled OH to 3810'

Ran 10 jts 3 1/2" OD 7.7# FJ-40 liner w BP
Guide Shoe. Bottom of liner @ 3810'. Top @3500'
6-29-77 Cmt. liner w/ 70sx cement. DO cmt. to 3500'6-30-77 DO cmt. Guide Shoe. CO to 3991'. Ran Baker
packer on 112 jts. of 2 3/8" EUE cmt lined tbg.

18. I hereby certify that the foregoing is true and correct

SIGNED

Wm. A. Burt

TITLE

ADMIN. SUPV.

DATE

5-18-77

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

*See Instructions on Reverse Side

ACCEPTED FOR RECORD

MAY 29 1977

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

USGS(5), MCA(4) File

RECEIVED

MAY 2 1977

COMM. & COMM. DIV.

100-100000-1000