

Form 100-10
(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions on reverse side)

Form approved
Product Form No. 41-1000
5. LEASE REGISTRATION AND SERIAL NO.
LC 029509 (4)
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form to drill or to deepen or plug back to a different reservoir. Use APPLICATION FOR PERMIT for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ **May 27 10 32 AM '69**
2. NAME OF OPERATOR **Water Injection well**
3. ADDRESS OF OPERATOR
Continental Oil Company
Box 460, Hobbs, New Mexico 88240
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface
1980' FNL 4660' FEL of sec. 22, T-17S,
R-32 E, in Lea County, N. Mex.
14. PERMIT NO. 15. ELEVATIONS (Show whether DF, ET, GS, etc.)
4007 DF
7. UNIT AGREEMENT NAME
MCA
8. FARM OR LEASE NAME
MCA Unit, Batters
9. WELL NO.
36
10. FIELD AND POOL, OR WILDCAT
McMurry G-S-A Region
11. SEC., T., R., E., M., OR BLM. AND SURVEY OR AREA
sec. 22, T-17S, R-32 E
12. COUNTY OR PARISH
Lea
13. STATE
N. Mex.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:			SUBSEQUENT REPORT OF:		
TEST WATER SHUT-OFF	☐	PULL OR ALTER CASING	☐	WATER SHUT-OFF	☐
FRACTURE TREAT	☐	MULTIPLE COMPLETION	☐	FRACTURE TREATMENT	☐
SHOOT OR ACIDIZE	☐	ABANDON*	☐	SHOOTING OR ACIDIZING	☐
REPAIR WELL	☐	CHANGE PLANS	☐	(Other) convert to water inj.	☒
(Other)	☐			(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

This well was converted to water injection by the following procedure. Verbal approval to convert this well was given by Mr. Gordon on February 17, 1969.

Cleaned out from 3992' to 3997'. Drilled out cement from 3997' to 4022'. Drilled on metal from 4022' to 4029'. Ran GR/N with caliper log from 4029' to 3000'. Ran 2 3/8" H-40 cement-lined tubing with packer. Displaced annulus with treated water and set packer at 3536'. Injected 1,000 BW in 24 hrs. on vacuum.

18. I hereby certify that the foregoing is true and correct

SIGNED M. E. Yeakley TITLE Administrative Section Chief DATE 5-16-69

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____
CONDITIONS OF APPROVAL, IF ANY: **APPROVED**

USGS-5

*See Instructions on Reverse Side

MAY 20 1969

J. L. GORDON
ACTING DISTRICT ENGINEER