

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
HOBBS, NEW MEXICO 88240

SUBMIT IN TRIPLICATE
(Other instructions
here side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ <u>Injection Well</u>		7. UNIT AGREEMENT NAME <u>MCA Unit</u>
2. NAME OF OPERATOR <u>Conoco Inc.</u>		8. FARM OR LEASE NAME <u>MCA Unit Bty3</u>
3. ADDRESS OF OPERATOR <u>P.O. Box 460 - Hobbs, New Mexico 88240</u>		9. WELL NO. <u>72</u>
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface <u>1980' F54 & 660' FWH - Unit Letter L</u>		10. FIELD AND POOL, OR WILDCAT <u>Maljama C-SA</u>
14. PERMIT NO. <u>30-025-00630</u>	15. ELEVATIONS (Show whether DF, RT, GR, etc.)	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA <u>22-17S-32E</u>
		12. COUNTY OR PARISH <u>Lea</u>
		13. STATE <u>NM</u>

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐
REPAIR WELL ☐	CHANGE PLANS ☐
(Other) ☐	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
(Other) ☒ <u>Cement to Cased Hole</u>	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Work started 9/12/88. POOL w/ Abq & pkr Set 4 1/2" RBP at 3585'. Clean out & jet wash to 4098'. Run fiberglass liner (4095'-3571') Cement w/ 180 sacks 50/50 po3 class "C" w/ .45 LB604 & .7% CaCl2. Magnum GT liner hanger/pkr at 3571'-74'. Run CBL-GR-CCl from 4089'-3200'. G1H perf w/ 2 1/8 gun 6th zone 3766'-3877' In total of 100 shots. Perf 7th zone 3907'-3970' In total of 62 shots and perf 9th zone 4080'-4090' In total of 22 shots. Acidize w/ 75 bbls 15% HCL-NE-FE. Run injection equipment. Work completed on 10/2/88

RECEIVED
DEC 15 11:38 AM '88
CARTER
ART.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] W. FINNEY

TITLE Administrative Supervisor

DATE December 14, 1988

(This space for Federal or State/office use)

ACCEPTED FOR RECORD

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

DEC 29 1988

*See Instructions on Reverse Side

SJS
CARLSBAD, NEW MEXICO