



← 25 sx cmt squeezed via thru perms 50' to surface

← 8-5/8" 28# @ 933'

top of salt 980'

← 75 sx cmt squeezed under packer 880' - 1,030'

base of salt 1,975'

← 25 sx cmt plug 1,925' - 2,025'

← 50 sx cmt sqz'd under retainer set @ 2,975'

← casing leaks 3,023' - 3,058' isolated 12/20/01

← CIBP @ 3,600' (set 12/20/01)

← 7" 20# H-40 @ 3,635'

← Open Hole to 4,139'

Field Name:			
County:	New Mexico	Well Type:	Oil
State:	Lea	Depth:	4,139
RRC District:		Drilling Commenced:	6/12/1944
Section:	22	Drilling Completed:	
Block:		Date Well Plugged:	
Survey:	T-17-S; R-32-E	Longitude:	
	1,980 FNL & 1,980 FEL	Latitude:	
		Freshwater Depths:	
API #:			
Lease or ID:			

Casing

Description	Size (inches)	Depth (feet)	TOC (feet)	Cement (sacks)	Hole Size (inches)
Surface:	8-5/8"	933	Surface	50	
Production:	7"	3,635	1,685	150	

Proposed Plugs

Description	Top (feet)	Depth (feet)	Volume (sacks)	Volume (cu ft)
1 CIBP (set 12/20/01)	3,600			0
2 Cement-Class C - Sqz/Retainer	2,975	3,058	50	66
3 Cement-Class C - Balanced	1,925	2,025	25	33
4 Cement-Class C - Sqz/Packer	880 (tag'd)	1,030	75	99
5 Cement-Class C - Sqz	surface	50	25	33

Perforations

Formation	Top (feet)	Depth (feet)
openhole intervals shot w/ nitro	3,677	4,107

Formations

Name	Top of Formation
top of salt	980
base of salt	1,975

Comments

12/14/01 - 12/21/01: Stripped tubing & rods OOH, CO wellbore to 3,630' and set CIBP. Isolated holes in casing 3,023 - 3,058' and set retainer to shut off 1/4 BPM water flow.

Prepared By: Jim Newman
Date: 1/18/2002

TRIPLE N
SERVICES INC.
MIDLAND, TX