

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPlicate
(Other instructions on
reverse side)Form approved.
Budget Bureau No. 42-R1424.5. LEASE DESIGNATION AND SERIAL NO.
LC 029509 (6)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

BAISH "B"

9. WELL NO.

5

10. FIELD AND POOL, OR WILDCAT

MALJ. W.C. MURROW11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA**SEC. 22, T-17S, R-32E**

12. COUNTY OR PARISH

LEA

13. STATE

N.M.

1.

OIL ☒ WELL GAS ☐ WELL OTHER ☐

2. NAME OF OPERATOR

CONTINENTAL OIL COMPANY

3. ADDRESS OF OPERATOR

Box 460, Hobbs, N.M. 882404. LOCATION OF WELL: Report location clearly and in accordance with any State requirements.
See also space 17 below.)

At surface

1980' FSL & 860' FWL OF SEC. 22

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4022' DF

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☒(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☒CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

This well is located 200' from an MCA water injection well. A water flow was recently discovered in the subject well; the following work is proposed: Clean out to ± 9050 & run CSBP on wireline, set @ $\pm 9,000'$ w/2 sks. cmt. on top. Test for leak. If no leak found, flange up wellhead & swage to 2" valve. If leak is found, set cmt. retainer 100' above leak & squeeze w/100 to 150 sks. Class "C" cmt. Leave 20' cmt above retainer. Pull plug, flange up wellhead & swage to 2" valve. Retain well in temp. abandon status as a possible replacement for MCA #72.

18. I hereby certify that the foregoing is true and correct

SIGNED

[Signature]

TITLE

SR. ANALYST

DATE

7-25-75

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

11565-5 MCA-4, File

[Signature]