


DUPLICATE

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico



## WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.

Deepening and work over of former injection well to be returned to production.

AREA 640 ACRES  
LOCATE WELL CORRECTLY

R. E. Fair

805 Missouri St. Artesia, N.M.

Baish

Well No. 4 in SW 1/4 of Sec. 22, T. 17S

R. 32E, N. M. P. M. Maljamar Field, Lea County.

Well is 660 feet North of the North line and 1980 feet west of the East line of Sec. 22-17-32

If State land the oil and gas lease is No. Assignment No.

If patented land the owner is Address

If Government land the permittee is Address

The Lessee is Address

Drilling commenced Oct. 24 1946 Drilling was completed Nov. 3 1946

Name of drilling contractor Beckman Inc. Address Odessa, Texas

Elevation above sea level at top of casing 3938' feet.

The information given is to be kept confidential until 19

## OIL SANDS OR ZONES

No. 1, from to No. 4, from 4045 to 4053

No. 2, from to No. 5, from 4057 to 4071

No. 3, from to No. 6, from 4083 to 4089

## IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

## CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	

## MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED

## PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set

Adapters—Material Size

## RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
	4 1/2"	Nitro	40 qts	11/2	4045-4058	
	3 1/2"	"	40 "	"	4058-4080	
	4 1/2"	"	40 "	"	4080-4093	4093 Total Depth

Results of shooting or chemical treatment Could not test before shot

## RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

## TOOLS USED

Rotary tools were used from 3997' feet to 4093' feet, and from feet to feet

Cable tools were used from feet to feet, and from feet to feet

## PRODUCTION

Put to producing Nov. 4 1946

The production of the first 24 hours was 54 barrels of fluid of which 99 % was oil; emulsion; % water; and 1 % sediment. Gravity, Be.

If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in.

## EMPLOYEES

Driller Driller

Driller Driller

## FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this

day of 19

Notary Public

Place

Date

Name

Position

## FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
3997	Old Total Depth		
3997	4045	48	Brown & Gray Lime
4045	4053	8	Brown Lime, Oil Pay, Slight Stain
4053	4067	14	Brown & Gray Lime
4067	4071	4	Gray Sand, slight Oil Stain
4071	4083	12	Brown & Gray Lime
4083	4089	6	Brown & Gray Lime- Fair Oil Stain & Porosity
4089	4093	4	Brown & Gray Lime
4093	Total Depth.		