

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENTNEW Mexico Oil Conservation District
1625 N. French Dr.
1. obs, NM 88249FORM APPROVED
OMB No. 1004-0135
Expires July 31, 1996SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter an
abandoned well. Use Form 3160-3 (APD) for such proposals.

SUBMIT IN TRIPLICATE - Other Instructions on reverse side

1. Type of Well
☐ Oil Well ☐ Gas Well ☒ Other Injection2. Name of Operator
Conoco, Inc.

3a. Address

10 Desta Dr. St. 100W, Midland, Tx 3b. Phone No. (include area code)
915-686-5580

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

UL-D, 660' FNL & FWL
Sec. 23, T-17S, R-32E

5. Lease Serial No.

LC058698B

6. If Indian, Allottee or Tribe Name

7. If Unit or C/A Agreement, Name and/or No.

8. Well Name and No.

M.C.A. Unit No. 31

9. API Well No.

30-025-00653

10. Field and Pool, or Exploratory Area

Maljamar GB-SA

11. County or Parish, State

Lea County, NM

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

- | | | | | |
|--|---|--|--|---|
| <input checked="" type="checkbox"/> Notice of Intent | <input type="checkbox"/> Acidize | <input type="checkbox"/> Deepen | <input type="checkbox"/> Production (Start/Resume) | <input type="checkbox"/> Water Shut-Off |
| <input type="checkbox"/> Subsequent Report | <input type="checkbox"/> Alter Casing | <input type="checkbox"/> Fracture Treat | <input type="checkbox"/> Reclamation | <input type="checkbox"/> Well Integrity |
| <input type="checkbox"/> Final Abandonment Notice | <input type="checkbox"/> Casing Repair | <input type="checkbox"/> New Construction | <input type="checkbox"/> Recomplete | <input type="checkbox"/> Other |
| | <input type="checkbox"/> Change Plans | <input checked="" type="checkbox"/> Plug and Abandon | <input type="checkbox"/> Temporarily Abandon | |
| | <input type="checkbox"/> Convert to Injection | <input type="checkbox"/> Plug Back | <input type="checkbox"/> Water Disposal | |

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 day following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

1. Spot 35' of cement on top of cement retainer at 3700'.
2. Circulate hole with gelled brine mud.
3. Spot 25 sxs of cement 1900'-2250'. TAG
4. Cut and pull the 4 1/2" casing at 850'.
5. Spot 25 sxs of cement (stub plug) 750'-950'. TAG
6. Perforate the 7" casing at 350'.
7. Circulate 275 sxs of cement thru perfs at 350' and fill hole to surface.
8. Install dryhole marker and clear location.

14. I hereby certify that the foregoing is true and correct

Name (Printed/Typed)

Don Fisher

Signature

Don Fisher

Title

Field Supervisor

Date

9-20-99

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

(ORIG. SGD.) ALEXIS C. SWOBODA

Title PETROLEUM ENGINEER

Date SEP 20 1999

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on reverse)

GWW

CURRENT WELLBORE

9/16/99

Elev. 4024' GL +1' KB

22' - 12 3/4" Casing. Cemented w/20 sxs. Circulated.

3005' - 7 " Casing. Cemented w/250 sxs. T.O.C. @ 1268'.

5 1/2" Scab Liner 2372'-3627'. Cemented w/52 sxs.

Cement Retainer @ 3700'

3860' - 4 1/2", 9.5#. Casing. Cemented w/325 sxs. T.O.C. @ 900'.

OH 3860'-4236'

Cement Plug 4150'-4236'

T.D. @ 4236'

CONOCO, INC.

M. C. A. No. 31

660' FNL & 660' FWL

Sec. 23, T-17S, R-32E

Lea County, NM

PROPOSED PLUG AND ABANDONMENT
9/16/99

Elev. 4024' GL +1' KB

22' - 12 3/4" Casing. Cemented w/20 sxs. Circulated.

CIRCULATE 275 SXS CEMENT THRU PERFS @ 350'
AND FILL HOLE TO SURFACE
PERFORATE THE 7" CSG. @ 350'

MUD

SPOT 25 SXS CEMENT STUB PLUG 750'-950'
CUT AND PULL 4 1/2" CSG. @ 850'

MUD

SPOT 25 SXS CEMENT 1900'-2250'

3005' - 7" Casing. Cemented w/250 sxs. T.O.C. @ 1268'.

MUD

5 1/2" Scab Liner 2372'-3627'. Cemented w/52 sxs.

SPOT 35' CEMENT ON TOP OF CMT. RET. @ 3700'

Cement Retainer @ 3700'

3860' - 4 1/2", 9.5#, Casing. Cemented w/325 sxs. T.O.C. @ 900'.

OH 3860'-4236'

Cement Plug 4'50'-4236'

T.D. @ 4236'

CONOCO, INC.

M. C. A. No. 31

660' FNL & 660' FWL

Sec. 23, T-17S, R-32E

Lea County, NM