

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Conoco, Inc.

3. Address and Telephone No.

10 Desta Dr., Suite 100W, Midland, Texas 79705 (915) 686-5424

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Sec. 23, T-17-S, R-32-E

1980 FNL & 1965 FEL

5. Lease Designation and Serial No.

LC 058698 B

6. If Indian, Ancestry or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Miller "B" #6

9. API Well No.

30-025-00655

10. Field and Pool, or Exploratory Area

Pearsall, Queen

11. County or Parish, State

Lea County, N.M.

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion or Well Completion or Recompletion Reports and Log forms.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Formerly the MCA Unit, Well #33

10-16-95: Run in hole w/7" cast iron bridge plug, set @ 1950', circulate mud, test casing to 1000#, spot 10 sx cement on top CIEP from 1950 - 1890'. Perforate well @ 1175', spot 25 sx from 1128 - 1078', perforate well @ 200', good circulation to surface in 8-5/8" casing.

10-17-95: Circulate 40 sx cement down 7" casing to 200' up 8-5/8" to surface, cut off wellhead, put in marker, rig down, clean location, move off.

(Class "C" cement, mud - 25#, Salt gel per bbl.

Cement retainer - 3450', 35' cement, RBP - 2200', 10' sand.

CIBP - 1950', 60' cement, 25 sx cement 1228 - 1078'.

40 sx 200' - surface 7 x 8-5/8").

14. I hereby certify that the foregoing is true and correct

Signed

Title

Ann E. Ritchie
Regulatory Agent

Date

11-10-95

(This space for Federal or State Office Use)

Approved by

Title

Conditions of approval, if any

Date