# V.M. OIL CONS. COMMISSION

4.0. BOX 1980

Form 3160-5 (June 1990)

### UNITED STATES DEPARTMENT OF THE INTERIOR

RECEIVED	S, NEW	MENICO	<b>88</b> 240
· · · · · · · · · · · · · · · · · · ·	. Bu	dget Bureau No.	1004-0135

BUREAU OF LAND MANAGEMENT Expires: March 31, 1993 5. Lease Designation and Serial No SUNDRY NOTICES AND REPORTS ON WELLS 10 50 14 50 Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. 058498R 6. If Indian, Allottee or Tribe Name Use "APPLICATION FOR PERMIT-" for such proposals SUBMIT IN TRIPLICATE 7. If Unit or CA, Agreement Designation Type of Well Well Gas Well 8. Well Name and No. Name of Operator MCA Unit No. 33 3 Address and Telephone No 9. API Well No. 10 Desta Dr. Ste 100W, Midland, TX 79705
4 Location of Well (Footage, Sec., T., R., M., or Survey Description) 10. Field and Pool, or Exploratory Area Maljamar Grayburg-SA
II. County or Parish, State 1980' FNL & 1965' FEL Sec. 23, T-17S, R-32E Lea CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12 TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandonmen: Change of Plans Recompletion New Construction Subsequent Report Plugging Back Non-Routine Fracturing Casing Repair Water Shut-Off Final Abandonment Notice Altering Casing Conversion to Injection Other Casing Dispose Water (Note: Report results of multiple completion on We 13 Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled. give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\* It is proposed to perform the following operations in order to prepare this well for temporary abandonment: POOH with production equipment. Set a cement retainer at 3450'. Circulate packer fluid to surface.

Notify the Carlsbad Blm Office 24 hrs. in advance of performing the pressure test. Ī. Pressure test casing to 500 psig for 30 minutes. This well will be recommended for temporary abandonment due to non-utility in the current waterflood. Wellbore access should be preserved due to uphole potential in the Queen 14. I hereby certury Title Conservation Coordinator

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements

Title

PETROLEUM ENGINEER

State office use

SGD.)

(ORIG.

Conditions of approval, if any

Approved by

## BUREAU OF LAND MANAGEMENT CARLSBAD RESOURCE AREA

#### Temporary Abandonment of Wells on Federal Lands

### Conditions of Approval

According to 43 CFR 3162.3-4-c, "No well may be temporarily abandoned for more than 30 days without the prior approval of the authorized officer".

Temporary Abandonment (TA) status approval requires a successful casing integrity test as follows:

- Contact the appropriate BLM office at least 24 hours prior to the scheduled Casing Integrity Test. For wells in Eddy County call (505) 887-6544; for wells in Lea County call (505) 393-3612.
- A bridge plug or packer shall be set at a maximum of 50 feet above any open perforations or open hole.
- 3. All downhole production/injection equipment (tubing, rods, etc.) shall be removed from the casing if they are not isolated by a packer.
- 4. The production casing shall be filled with corrosion inhibited fluid and pressure tested to 500 psi. The casing shall be capable of holding this pressure for at least 30 minutes with a 10% allowable leak-off.

Wells that successfully pass the casing integrity test will be approved for Temporary Abandonment (TA) status for 12 months provided that the operator:

- 1. Submits a subsequent Sundry Notice requesting TA approval,
- 2. Attaches a clear copy or the original of the pressure test chart,
- 3. And attaches a detailed justification why the well should not be plugged and abandoned.

The TA status could be extended without another casing integrity test provided there was no leak-off during the test.

If the well does not pass the casing integrity test, then the operator shall within 30 days submit to BLM for approval one of the following:

- A procedure to repair the casing so that a TA approval can be granted.
- 2. A procedure to plug and abandon the well.