

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE
(Other instructions on
reverse side)

Form approved
Budget Bureau No. 42 R1424

5. LEASE DESIGNATION AND SERIAL NO.
LC 058697 (a)
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ WATER INJECTION WELL
2. NAME OF OPERATOR Continental Oil Company
3. ADDRESS OF OPERATOR Box 460, Hobbs, N.M. 88240
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

7. UNIT AGREEMENT NAME

MCA

8. FARM OR LEASE NAME

MCA Unit

9. WELL NO.

80

10. FIELD AND POOL, OR WILDCAT

MALG-5A

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec 23 T-17S R-32E

14. PERMIT NO. 660' FSL & 660' FEL OF Sec 23

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4021' DF

12. COUNTY OR PARISH

LEA

16. STATE
N.M.

18. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

DF ELEV: 4021'
CSG: 4-1/2" AT 3334'

DF ELEV: SAME
CSG: 4-1/2" AT 3334' W/3-1/2"
LINER FROM 3650'-4025'

FORMATION: SAN ANDRES
TESTED: 500 BWPD
WORK STARTED: 12-30-76
WORK DONE: CO TO 4237'. PB TO 4199' W/150 SKS CLASS "H" CMT.
FILLED OH W/PEA-GRAVEL TO 4030'. CAPPED W/8' CAL-SEAL CAP.
RAV & SET 375' (11 JTS) 3-1/2" 8.81# N-80 FJ HYDRIL LINER W/50
SKS CLASS "C" CMT. LINER SET AT 4025'. TOL AT 3650'. CO CMT &
TREATED TOL TO 1000#. CO TO 4030' & TESTED BTM OF LINER TO
1000#. DO PEA-GRAVEL & CMT TO 4200'. RAV 116 JTS 2-3/8" CL TSG.
FILLED ANNULUS W/PKR FLUID & SET PKR AT 3607' UNDER 10 PTS
TENSION. CONNECTED FOR INJECTION.
LOCATION: 660' FSL & 660' FEL OF SECTION 23, T-17S, R-32E

18. I hereby certify that the foregoing is true and correct

SIGNED

Wm. A. Burtch

TITLE

ADMIN. SUPV.

DATE

5/18/77

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD

MAY 24 1977

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

*See Instructions on Reverse Side

11505 (c) m-a-11-77