

DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO.

2C 058698 (6)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

MCA

8. FARM OR LEASE NAME

MCA Unit

9. WELL NO.

34

10. FIELD AND POOL, OR WILDCAT

Magowan Reservoir

11. SEC., T., R., M., OR BLM. AND SURVEY OR AREA

Sec. 23, T-17S, R-32E

12. COUNTY OR PARISH

Tex

13. STATE

N. Mex.

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Water Injection Well

2. NAME OF OPERATOR

Continental Oil Company

3. ADDRESS OF OPERATOR

Box 460, Hobbs, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)

At surface

2051' FNL & 1909' FNL of Sec. 23, T-17S, R-32E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, CR, etc.)

4019' DF

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Convert to water injection

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

This well was converted to a water injection well by the following procedures. Verbal approval to convert this well was given by Mr. Borden on February 17, 1969.

Cleaned out well from 3933' to 4174'. Ran GR/N with caliper log from 4174' to 3,000'. Ran 2 3/8" cement lined tubing with packer. Displaced annulus with treated water and set packer at 3588'. Placed well on injection.

18. I hereby certify that the foregoing is true and correct

SIGNED

M. E. Yeakley

TITLE Administrative Section Chief

DATE 4-14-69

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED

DATE

APR 15 1969

*See Instructions on Reverse Side

J. L. GORDON
ACTING DISTRICT ENGINEER