

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY O.C.C.

SUBMIT IN TRIPI
(Other instructions
reverse side)

JE
re-

Form approved,
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 059152 (b)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Johns "B" DE

9. WELL NO.

5

10. FIELD AND POOL, OR WILDCAT

Maljamar

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

24-T17S-R32E

12. COUNTY OR PARISH

Lea

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. ☐ OIL WELL ☐ GAS WELL ☒ OTHER
Sinclair Oil Corporation Merged
into Atlantic Richfield Company
Water Injection Well
effective March 4, 1969

2. NAME OF OPERATOR
Sinclair Oil & Gas Company

3. ADDRESS OF OPERATOR
P. O. Box 1920, Hobbs, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface
1960 feet from North line and 660 feet from East line
of Section 24-T17S-R32E, Lea County., New Mexico

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4080' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(or)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Convert oilwell to WIW

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

X

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

3-25-66 Cleaned out w/drilling bailer 4224-4279' PBTD. Ran 4106' of 2-3/8" CD Plastic Coated (TK90) w/Model R Packer, seat nipple 4098'.
Injected 100 bbls. fresh water into Grayburg formation thru perforations 4135-40', 4156-61', 4180-99' and 4258-66' in 12 hrs. on vacuum. Converted from producing well to Water Injection Well in Sinclair Maljamar Johns DE Waterflood. Effective 3-26-66.

APPROVED

APR 6 1966

J. L. GORDON
ACTING DISTRICT ENGINEER

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Superintendent

DATE

4-5-66

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

Orig&2cc: USGS
cc: Regional Office
cc: file