

Form 10-53,
May 1965

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPI
(Other instructions
verse side)

FE-
re-

Form approved,
Budget Bureau No. 42-R1424

5. LEASE DESIGNATION AND SERIAL NO.

LC 059152 (b)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Johns "B" DE

9. WELL NO.

12

10. FIELD AND POOL, OR WILDCAT

Maljamar

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

24-T17S-R32E NM PM

12. COUNTY OR PARISH

Lea

13. STATE

New Mexico

1.

OIL WELL ☐ GAS WELL ☐ OTHER ☐

Water Injection Well

2. NAME OF OPERATOR

Sinclair Oil & Gas Company

3. ADDRESS OF OPERATOR

P. O. Box 1920, Hobbs, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)

At surface

660 feet from North line and 660 feet from West line of
Section 24-T17S-R32E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4073' GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) Convert oilwell to WIW ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

X

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

3-26-66 PBL 4362'. Jet perforated Grayburg 4136-40' w/8 - 3/8" holes. Ran 2-3/8" CD tubing and packer to 4133' and Ret. Bridge Plug @ 4150'. M.A. washed Grayburg perforations 4136-40' w/250 gals. M.A. All on vacuum. Ran 2-3/8" CD tubing, packer and set @ 4063', seat nipple @ 4060' (plastic coated tubing). Injected 180 bbls. fresh water into Grayburg thru perforations 4103-13', 4121-31', 4136-40' and 4164-69' in 12 hours. All on vacuum. Converted from producing well to water injection well in Sinclair Maljamar Johns DE Waterflood. Effective 3-27-66.

APPROVED

APR 6 1966

J. L. GORDON

ACTING DISTRICT ENGINEER

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Superintendent

DATE

4-5-66

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side Orig & 2cc: USGS

cc: Regional Office

cc: file