
GPO 9 18 507



(SUBMIT IN TRIPLICATE)

UNITED STATES

DEPARTMENT OF THE INTERIOR

GEOLOGICAL SURVEYS 1:07 2 AM 8:10

Land Offic	. Lan	Craso	進
Lesse No.			(b)
Unite 1	Sees	·	
f:a	•		

		SUBSEQUENT REPORT OF WATER SHUT-OFF	
OTICE OF INTENTION TO CHANGE	PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
OTICE OF INTENTION TO YEST WA	ATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING.	
OTICE OF INTENTION TO RE-DRILL	L OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
OTICE OF INTENTION TO SHOOT O	OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR	R ALTER CASING	SUPPLEMENTARY WELL HISTORY	
OTICE OF INTENTION TO ABANDON	N WELL		
(INDIC	CATE ABOVE BY CHECK MA	ARK NATURE OF REPORT, NOTICE, OR OTHER DATA)	
ème B		October 23	, 19 .2
ell No. 12 is loca	ated 460 ft. fro	om $\begin{bmatrix} N \\ W \end{bmatrix}$ line and $\begin{bmatrix} 660 \\ W \end{bmatrix}$ ft. from $\begin{bmatrix} W \\ W \end{bmatrix}$ line of sec	. 24
WW/A Section 24		(**)	
(34 Sec. and Sec. No.)	(Twp.)		
Field)	(Conn	ty or Subdivision) (State or Territory)	-
agges were total de 4 1174-80 with A 4	at about a year fi	eiro lino. Perferated 4 1/2" caming a	t 4130
d \$173-80 with b jo mbbed load. Treate O gallene regaler a o 7 hours through lo	ot shots pur fi ed down casting eald, After re	with 30,000 gallone free oil, 60,0000 coovering load oil flewed 65 bbls oil, th GOR of 1017 and flewing tubing pres	send no we
d \$173-80 with b jo mbbed load. Treate O gallene regaler a o 7 hours through lo	ot shots pur fi ed down casting eald, After re	with 30,000 gallons free oil, 60,000 servering lead oil flewed 65 bbls oil, th GOR of 1017 and flewing tubing pres	acid send no wa euro c
nd 4179-80 with 5 jo mbbed load. Treate 10 gallene regular s 1 7 hours through 10	ot shots pur fi ed down casting eald, After re	with 30,000 gallons free oil, 60,000 secovering lead oil flewed 65 bbls oil, th GOR of 1017 and flewing tubing pres	acid sand no wa
nd 4179-80 with b jo mbbed load. Treate 10 gallene regalar a 1 7 hours through 10	ot shots pur fi ed down casting eald, After re	with 30,000 gallons free oil, 60,000 servering lead oil flewed 65 bbls oil, th GOR of 1017 and flewing tubing pres	acid sand no wa
nd 4179-80 with 5 jo mbbed load. Treate 10 gallene regular s 1 7 hours through 10	ot shots pur fi ed down casting eald, After r	with 30,000 gallons free oil, 60,000 secovering lead oil flewed 65 bbls oil, th GOR of 1017 and flewing tubing pres	acid sand no wa
nd 4173-80 with 4 jo mbbe: load. Treate 30 gallene regular a 17 hours through 1/ 25%.	ot shots par f ad down casting acid. After r 6/64" choke wi	with 30,000 gallons free oil, 60,000 ecovering lead oil flewed 65 bbls oil, th GOR of 1017 and flewing tubing pres	acid send ne wa leare c
nd \$173-60 with 5 journeys load. Treate to gallene regalar as 7 hours through 1625%.	ot shots par f ad down casting acid. After r 6/64" choke wi	with 30,000 gallane free oil, 60,000 ecovering lead oil flowed 65 bbls oil, th GOR of 1617 and flowing tubing pres	acid send ne wa leare c
and \$173-80 with 5 journed load. Treate 20 gallene regular at 7 hours through 1625%.	ot shots pur fi ed down casting sold. After re 6/64" shoke wit	with 30,000 gallane free oil, 60,000 ecovering lead oil flowed 65 bbls oil, th GOR of 1617 and flowing tubing pres	acid send ne wa leare c
at 4173-80 with 4 journeys load. Treate 10 gallene regular at 7 hours through 1625%. Tunderstand that this plan of woompany Drilling & 2000 many Drilling &	of shots par find down casing sold. After re- folds shoke will be shoked with the shoke will be shoked with the shoke will be shoked with the shoked will be showed with the showed will be	with 30,000 gallane free oil, 60,000 ecovering lead oil flowed 65 bbls oil, th GOR of 1617 and flowing tubing pres	acid send no we leare c
id 4173-80 with 4 jumble: lead. Treate 10 gallens regalar: 17 hours through 16 15%. 1 understand that this plan of wo 1 mpany Drilling & 2 1 dress Box 2075	of shots par find down casing sold. After re- folds shoke will be shoked with the shoke will be shoked with the shoke will be shoked with the shoked will be showed with the showed will be	with 30,000 gallane free oil, 60,000 covering lead oil flewed 65 bbls oil, th GOR of 1017 and flewing tubing pressure of the company, Inc.	sand sand no w