

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPL  
Other instructions  
(Reverse side)

Form approved.  
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or to change to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR Sinclair Oil & Gas Company		8. FARM OR LEASE NAME Johns "A" 24 DE	
3. ADDRESS OF OPERATOR P. O. Box 1920, Hobbs, New Mexico		9. WELL NO. 2	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660 feet from the South line and 1980 feet from the West line of Section 24-T17S-R32E NM PM		10. FIELD AND POOL, OR WILDCAT Maljamar	
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 24-T17S-R32E		12. COUNTY OR PARISH Lea	
13. STATE New Mexico		14. PERMIT NO.	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4040' GR		16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data	

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
(Other) ☒ Run 4-1/2"OD Csg, log, perf. & X Acidize.

PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
ABANDON\* ☐  
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐  
FRACTURE TREATMENT ☐  
SHOOTING OR ACIDIZING ☐  
(Other) ☐  
REPAIRING WELL ☐  
ALTERING CASING ☐  
ABANDONMENT\* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Present Total Depth: 4332'. PBTD 4265'. Well presently completed in Grayburg San Andres 3787-4265' Open Hole producing 4 BOPD and no water. 7"OD 22# Csg set @ 3787'.

PROPOSE TO: Run 4-1/2"OD 11.60# J-55 casing to TD 4332' and cement w/approximately 300 sacks and tie into 7"OD casing @ 3500'. Log and perforate approx. 3800-4332'. Acidize w/approx. 250 gals. each interval, test, run tubing and packer, nipple up to inject water. Convert from oilwell to water injection well in Sinclair Maljamar Johns Waterflood Project.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature]

TITLE Superintendent

DATE 2-16-66

(This space for Federal or State office use)

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED  
FEB 21 1966  
A. B. DRAVINS  
DISTRICT ENGINEER

\*See Instructions on Reverse Side

Originals: USGS  
cc: Regional Office  
cc: file