

COPY TO O. C. C.
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TR
(Other instruction
reverse side)DATE*
on re-Form approved,
Budget Bureau L.S. 42-14124.

5. LEASE DESIGNATION AND SERIAL NO.

LC 030437 (a)

6. IF INDIAN, ALLOTTEE OR EREE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐		7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR Atlantic Richfield Company		8. FARM OR LEASE NAME Johns A-24 DE	
3. ADDRESS OF OPERATOR P. O. Box 1710, Hobbs, New Mexico 88240		9. WELL NO. 3	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' FSL & 1980' FEL (Unit letter O)		10. FIELD AND POOL, OR WILDCAT Maljamar Grayburg	
14. PERMIT NO.		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 24-17S-32E	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4045' GR		12. COUNTY OR PARISH Eddy Lea	
		13. STATE N.M.	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) Plug & Abandon ☒REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

RU 4/12/78. On 4/19/78 inst BOP. Ran 4-1/2" OD csg wash pipe & washed over stuck 2-3/8" OD EUE tbgs & rods to 3590', rec 3493' of 2-3/8" OD tbgs & 3505' rods. Milled out of 7" OD csg @ 3540'. Had water flow of 720 BPD after milling out of 7" OD csg @ 3540'. RIH w/cmt retr, set retr @ 3112'. Ran csg insp & Sonar log 3109' to surf, indicated water flow around retr. Reset retr @ 2696', no water shut off. Cmtd thru retr @ 2696' w/12 bbls Halliburton Flo-chek, 40 sx Cl C cmt cont'g 6#/sk salt & 2% CaCl, 10 bbls Flo-chek, 40 sx cmt, 10 bbls Flo-chek, 40 sx cmt, 10 bbls Flo-chek, 30 sx cmt. Shut off water flow & press up to 1000 PSIG. No water flow. POH w/tbgs. WIH w/6-1/8" bit, drld hard cmt 858-1217'. POH w/bit. No water flow. WIH w/2-7/8" tbgs OE, spotted 60 sx Cl C cmt cont'g 6# /sk salt 1217-857'. Perf'd 4 squeeze holes @ 190', unable to establish circ. Spotted 35 sx Cl C cmt plug 220' to surf. Pmpd 40 sx Cl C cmt down 10-3/4" x 7" annulus. Final pump press 150#. Installed regulation dry hole marker. Well P&A Eff 5/10/78. Final Report.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Dist. Drlg. Supt.

DATE 5/15/78

(This space for District or State office use)

APPROVED

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

JUN 13 1980

ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side