

(SUBMIT IN TRIPLICATE)

Land Office **Las Cruces**Lease No. **L C 030437 (a)**Unit **RECEIVED**

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

NOV 2 1960

## SUNDRY NOTICES AND REPORTS ON WELLS

D. C. D.  
DISTRICT OFFICE

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	X
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	X
NOTICE OF INTENTION TO ABANDON WELL.....		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Johns A-24

November 12, 1958

Well No. 4 is located 660 ft. from XPS line and 660 ft. from E line of sec. 24SE/4 Section 24  
(1/4 Sec. and Sec. No.)17S  
(Twp.)32E  
(Range)NMPM  
(Meridian)Pearceall  
(Field)Lea  
(County or Subdivision)New Mexico  
(State or Territory)The elevation of the derrick floor above sea level is 4070 ft.

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

The 7" oil string run in May 1943 was cemented with two-stage cementing collar at 1100 feet and cemented with 100 sacks cement around shoe and 250 sacks through two-stage port.

The subject well was plugged and abandoned as follows:

Ran tubing with Halliburton retrievable squeeze tool set at 3370'. Squeezed with 50 sacks regular cement with maximum pressure of 2900#. WOC 16 hours and pressure tested squeeze plug with 2800#, held O.K. Spotted cement plug from 3476 to 3711' with 50 sacks cement. Filled hole with 10# mud and pulled tubing. Shot and pulled 7" casing from 400'. Ran tubing and spotted plug across shot point with 15 sacks regular cement and across 10 3/4" casing shoe at 137 feet with 10 sacks regular cement. Spotted 5 sack plug in top of 10 3/4" casing and erected 4' X 4" monument. Filled cellar and cleared and leveled location.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Drilling & Exploration Company, Inc.Address Box 2075Hobbs, New MexicoBy D. C. D.Title Division Production Superintendent