



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Las Cruces
Lease No. 18 030437 (a)
Unit 18020

SUNDRY NOTICES AND REPORTS ON WELLS

| | | | |
|--|-------------------------------------|--|-------------------------------------|
| NOTICE OF INTENTION TO DRILL | | SUBSEQUENT REPORT OF WATER SHUT-OFF | |
| NOTICE OF INTENTION TO CHANGE PLANS | | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING | |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF | | SUBSEQUENT REPORT OF ALTERING CASING | |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL | | SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR | |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE | | SUBSEQUENT REPORT OF ABANDONMENT | |
| NOTICE OF INTENTION TO PULL OR ALTER CASING | | SUPPLEMENTARY WELL HISTORY | <input checked="" type="checkbox"/> |
| NOTICE OF INTENTION TO ABANDON WELL | <input checked="" type="checkbox"/> | | |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Johns A-24

October 22, 1958

Well No. ▲ is located 660 ft. from 100 line and 660 ft. from E line of sec. 24
33 1/4 Section 24 173 123 180°W
 (1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Pearson Lee New Mexico
 (Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 4070 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Set Halliburton HRC tool at 3375 and squeezed off perforations 3440-42 (red sand) with 150 sacks regular cement in two stages. Pulled squeeze tool and ran bit. Drilled out cement, unable to get below 3675. Attempted to run snodge through collapsed casing. Unable to get below 3675.
 We now propose to plug subject well to abandon as follows: Squeeze cement at 3675 with 100 sacks; cut and pull 7" casing from approximately 3350; spot cement plug across base of Salt Section with 25 sacks; spot cement plug across top of Salt Section with 25 sacks; spot plug across bottom of 10 3/4" casing with 25 sacks; spot 5 sack plug in top of 10 3/4" casing with marker, remainder of hole to be filled with 100 mud.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Drilling & Exploration Company, Inc.Address Box 20775Albuquerque, New MexicoBy J. C. SmithTitle Division Production Superintendent