

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions reverse side)Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO.

LC-058697 (6)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

MCA

8. FARM OR LEASE NAME

MCA Unit

9. WELL NO.

137

10. FIELD AND POOL, OR WILDCAT

Maj. B-SA Bays

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 25 T-17S R-32E

12. COUNTY OR PARISH 13. STATE

Lea

N. Mex.

1.

OIL WELL ☐ GAS WELL ☐ OTHER ☒ Water Injection Well

2. NAME OF OPERATOR

CONTINENTAL OIL COMPANY

3. ADDRESS OF OPERATOR

P. O. Box 460, Hobbs, N.M. 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

660' FNL + 660' FWL of Sec. 25

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4017' DF

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☒SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☒ Deepen & Inst. Casing or LinerPULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

It is proposed to deepen in the same zone from 4193' PDD to a new TD of 4,250'. Run casing inspection log. Log shows 5 1/2" casing to be in an unsatisfactory condition. A new string of 4 1/2" OD 10.23# casing will be run to ± 4,000' and cemented with 175 sacks Class C Cement. If 5 1/2" casing is in good condition a 4 1/2" OD 10.23# liner will be run from ± 3,700' to ± 4,000' and cemented with 50 sacks of Class C Cement. Well to be fraced with 20,000 gal. gelled brack water & 40,000# sand. Well to be placed back on injection.

18. I hereby certify that the foregoing is true and correct

SIGNED

SK Allent

TITLE

Alternate For
Division Office Manager

DATE 7-25-74

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED

JUL 30 1974

ARTHUR R. BROWN
DISTRICT ENGINEER

USBS-5, MCA-3, File

*See Instructions on Reverse Side