Form	9-331
(May	1963)

## 'SIAIES SUBMIT IN TRIPLICA' THE INTERIOR (Other instructions of verse side) UNITED STATES DEPARTMENT

GEOLOGICAL SURVEY

Form approved.

6. IF INDIAN, ALLOTTEE OR TRIBE

		Danker Da	itean 14	U. 44-K1467
5.	LEASE	DESIGNATI	ON AND	SERIAL NO.
1	-	05	9/19	テクしん
_	_		, ,	

<b>SUNDRY</b>	<b>NOTICES</b>	AND	<b>REPORTS</b>	ON WELLS	

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.

Use "APPLICATION FOR PERMIT—" for such proposals.)

7. UNIT AGREEMENT NAME

8. FARM OR LE

1980 FAL & 660 FEL

14. PERMIT NO.

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

AME OF OPERATOR

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NJECTION ILLELL

NOTICE OF INTENTION TO:

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\* CHANGE PLANS

WATER SHUT-OFF FRACTURE TREATMENT REPAIRING WELL

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Deepened from 4260 to 4279. Treated OH W/500 98/s 15% Acid & 2000 gals total fresh wto. Frac w/10,000 gals total gelled wtr. Dumped per gravel to 3850'. Washed out to 4025'. Ran 4" Hydril "FJ" csq to 4032'. Cmt w/75 sks Class "C". Drilled out cont 2735'- 4039' & cleaned out to TD. Raw cont lined thus a set 4" tension phr. @ 3942'. Rosumed injection. Workaver started 7-8.75, completed 7-30-75

foregoing is true and correct

SR. ANALYST

(This space for Federal or State office use)

APPROVED BY CONDITIONS OF APPROVAL, IF ANY: TITLE

\*See Instructions on Reverse Side

ACCEPTED FOR RECORD U. S. GEOLOGICAL S HOBBS, NEW MEXICO

4565-5 MCA.4, File