

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE*
(Other instructions reverse side)Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. UNIT AGREEMENT NAME MCA
2. NAME OF OPERATOR CONTINENTAL OIL COMPANY	8. FARM OR LEASE NAME MCA UNIT
3. ADDRESS OF OPERATOR Box 460, HOBBS, N.M. 88240	9. WELL NO. 193
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 2615' FSL & 2615' FEL OF SEC. 25	10. FIELD AND POOL, OR WILDCAT MALJ. G-SA REPRESS.
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3994' DF
	11. SEC., T., E., M., OR BLK. AND SURVEY OR AREA SEC. 25, T-17S, R-32E
	12. COUNTY OR PARISH LEA
	13. STATE N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☒
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐
REPAIR WELL ☐	CHANGE PLANS ☐
(Other) INSTALL CASING	☒

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
(Other) ☐	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Due to poor condition of production casing in this well, the following procedure is proposed: Set Lyner OH BP @ 4090' w/10' sand on top. Run 4080' of 4 1/2" OD 9.5# K-55 casing. Set @ ± 4080' w/200 sks. Class "C" cement. WOC, drill out shoe, & test to 750#. If necessary, squeeze w/ 75-100 sks Class "C" cement. Drill out & push OH BP to TD. Return to production.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

SR. ANALYST

DATE

3-13-75

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED

MAR 1 1975

JIM SIMS
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

USGS/5, MCA-3, File