

N. M. OIL CONS. COMMISSION

Form Approved.
Budget Bureau No. 42-R1424

UNITED STATES BOX 1980
HOBBS, NEW MEXICO 88240
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐
well well

2. NAME OF OPERATOR
CONOCO INC.

3. ADDRESS OF OPERATOR
P. O. Box 460, Hobbs, N.M. 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FNL & 1980' FEL
AT TOP PROD. INTERVAL: ☒
AT TOTAL DEPTH: ☒

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) Install 5" CSG ☒

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☐
☒

LEASE

LC-058408(a)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

MCA Unit

8. FARM OR LEASE NAME

MCA Unit Bldg 4

9. WELL NO.

142

10. FIELD OR WILDCAT NAME

Maljamar (G/SA)

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 26, T-17S R-32E

12. COUNTY OR PARISH

Lea

13. STATE

N.M.

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

(NOTE: Report results of multiple completion zone change on Form 9-330.)

OIL & GAS
MINERALS MGMT. SERVICE
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

MIRU 9-27-82.

Pear 77 Sx sd down CSG. RU & run 104 jts 5" 13# K-55

CSG. Tag sd at 4090'. CSG shoe set at 4086'. FC at 4047'.

Cmt w/300 Sx class 'C' w/4% gel, 1/2 of 1% friction reduce,

3# salt & 1/2# FLA per gal lead cmt & 50 Sx class 'C' w/1/2

of 1% friction reduce, 3# salt, 3# sd & 1/2# FLA per Sx. Circ. 100 Sx.

Cut off 5" CSG & install CSG spec. Tested: 2460, 218W 10-13-82, 24 hrs.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Wm. A. Butterfield TITLE Administrative Supervisor DATE 10-21-82

ACCEPTED FOR RECORD (Use for Federal or State office use)

APPROVED BY PETER W. CHESTER TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF JAN 17 1983

MINERALS MANAGEMENT SERVICE
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side

RECEIVED

JAN 14 1983

**O.L.B.
HOBBS OFFICE**