

N

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

Foundation, Fair & Pope

Box 2, Loco Hills, New Mexico

Company or Operator

Address

Johns

Well No. 2A

in NWNE 1/4 of Sec. 26

T. 17 S

Lease

R. 32 E

N. M. P. M.

Maljamar

Field, Lea

County.

Well is 660 feet south of the North line and 1980 feet west of the East line of Sec 26-17S-32E

If State land the oil and gas lease is No.

Assignment No.

If patented land the owner is

Address

If Government land the permittee is Ruth Day Johns

Address ?

The Lessee is Foundation, Fair & Pope

Address Box 689, Tyler, Texas

Drilling commenced December 24

19 42

Drilling was completed

March 4, 43

Name of drilling contractor Suppe & Suppe

Address Tulsa, Oklahoma

Elevation above sea level at top of casing feet.

The information given is to be kept confidential until Not confidential

19

OIL SANDS OR ZONES

No. 1, from 3830 to 3835

No. 4, from to

No. 2, from 4005 to 4010

No. 5, from to

No. 3, from 4120 to 4139

No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 735 to 835 feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
10"				720'		720'			Shut off water
8 1/2"	28#	11	Lapwell	1179'		Cemented			Salt Strg
7"	20#	8 rd	SmLess	3739'	Larkin	Cemented			Oil Strg
2"		8 rd		4125'					tubing

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
	8 1/2"	1179'	50	Halliburton		
8"	7"	3739'	100	"		6 tons
6"	2"	4125'		Tubing		

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set

Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
		Nitro	240 qts	3-8-43	4022-4144	4150

Results of shooting or chemical treatment Increased production to where it tested
56 barrels first two hours. No water.

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from feet to feet, and from feet to feet

Cable tools were used from 0 feet to 4174 feet, and from feet to feet

PRODUCTION

Put to producing March 13th 19 43

The production of the first 24 hours was 56 barrels of fluid of which 100 % was oil; %
emulsion; % water; and % sediment. Gravity, Be

If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in.

EMPLOYEES

Driller Driller
Driller Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 20th

Subscribed and sworn to before me this 20th 43

day of March 19 43

Name O. M. Pope

Position Manager

Representing Foundation, Fair & Pope

Company or Operator

Address Box 689, Tyler, Texas.

My Commission expires

Notary Public

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	190	190	Red Rock
190	200	10	Anhy
200	250	50	Brown Shale
250	270	20	Anhy
270	735	465	Red Rock
735	835	100	Sand & Rock
835	885	50	Red Rock
885	890	5	Sand
890	970	80	Red Rock
970	1168	198	Anhy & Red Rock
1168	1175	7	Sand
1175	1190	15	Anhy
1190	1975	785	Salt
1975	2370	395	Salt & Anhy
2370	3285	915	Anhy & Red Rock
3285	3330	45	Red Sand
3330	3565	235	Anhy & Red Rock
3565	3585	20	Red Sand
3585	3640	55	Anhy & Red Rock
3640	3645	5	Brown Lime
3645	3680	35	Anhy & Red Rock
3680	3830	150	Gray Lime
3830	3835	5	Lime- Show Oil
3835	3965	130	Grey Lime
3965	4005	40	Sandy Lime
4005	4010	5	Sandy Lime- Show Oil & Gas
4010	4080	70	Gray Lime
4080	4085	5	Sandy Lime-Gas
4085	4120	35	White Lime
4120	4139	19	Sandy Lime-Oil & Gas
4139	4174	35	White Lime-T. D.