

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ *Water Supply*

2. NAME OF OPERATOR *Continental oil Co.*

3. ADDRESS OF OPERATOR *Box 460 Hobbs, N. Mexico*

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface
1980' FNL and 660' FWL of Sec 26

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3964' df

5. LEASE DESIGNATION AND SERIAL NO.
LC-058698 (a)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME
MCA

8. FARM OR LEASE NAME
MCA Unit

9. WELL NO.
144

10. FIELD AND POOL, OR WILDCAT
Seven Rivers Queen

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec 26, T-17S, R-32E

12. COUNTY OR PARISH
Lea

13. STATE
N. Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐ PULL OR ALTER CASING ☐
FRACTURE TREAT ☐ MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐ ABANDON* ☐
REPAIR WELL ☐ CHANGE PLANS ☐
(Other) ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐ REPAIRING WELL ☐
FRACTURE TREATMENT ☐ ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐ ABANDONMENT* ☐
(Other) *Converting to wtr supply* ☒
(NOTE: Report results of multiple completion or Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled cement from 3530' to 3755'. Drilled BP at 3830'. Spotted 160 socks class C cement and tagged cement plug at 3960'. Spotted 250 socks class C cement and tagged cement at 3278'. Drilled out to 3496'. Perf w/15' spf at 2810'-15' and 3475'-3490'. Set packer at 2717' and treated perfs 2810'-15' and 3475'-90' w/4000 gals 28% HCL-NE acid. Completed -10-16-72

18. I hereby certify that the foregoing is true and correct

SIGNED

Robert Gault

TITLE

Admin. Supervisor

DATE

11-17-72

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD

DEC 1 1972

U. S. GEOLOGICAL SURVEY,
HOBBS, NEW MEXICO

*See Instructions on Reverse Side

11505-5 MCA-3 E.P.