

DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

(Other instructions on reverse side)

5. LEASE DESIGNATION AND SERIAL NO.

LC 058698

6. INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Continental Oil Company

3. ADDRESS OF OPERATOR

P. O. Box 460, Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface

1980' FNL and 660' FWL of sec 26

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, CR, etc.)

3764' df

7. UNIT AGREEMENT NAME

MCA

8. FARM OR LEASE NAME

MCA Unit #4

9. WELL NO.

144

10. FIELD AND POOL, OR WILDCAT

MCA G-SA Repres

11. SEC., T., R., M., OR B.L. AND SURVEY OR AREA

Sec 26, T-17S, R-32E

12. COUNTY OR PARISH

Lea

13. STATE

N. Mex

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐

PULL OR ALTER CASING

☐

FRACTURE TREAT

☐

MULTIPLE COMPLETION

☐

SHOOT OR ACIDIZE

☐

ABANDON*

☐

REPAIR WELL

☐

CHANGE PLANS

☐

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐

REPAIRING WELL

☒

FRACTURE TREATMENT

☐

ALTERING CASING

☐

SHOOTING OR ACIDIZING

☐

ABANDONMENT*

☐

(Other)

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Set OH bridge plug at 3586' and cement retainer at 3400'. Pumped in 100 sacks diesel oil cement and 100 sacks class C cement w/ 3# salt. Went in hole w/ cement retainer and set at 3368'. Squeezed 3368' - 3750' w/ 150 sacks class C cement w/ 3# salt per sack. Tested casing w/ 1000 psi. Held O.K. Remainder of work will be performed and submitted under a new intention after inject profiles.

18. I hereby certify that the foregoing is true and correct

SIGNED

Hugh Dwyer

TITLE Administrative Supervisor

DATE

12-28-71

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

USGS (5) File MCA(3)

*See Instructions on Reverse Side

DEC 30 1971
GEOLOGICAL SURVEY
HOBBS, NEW MEXICO