

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE
(Other instructions on reverse side)Form approved
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Injection Well	7. UNIT AGREEMENT NAME MCA
2. NAME OF OPERATOR Continental Oil Company	8. FARM OR LEASE NAME MCA Unit #4
3. ADDRESS OF OPERATOR P.O. Box 460, Hobbs, N.M.	9. WELL NO. 142
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980' FWH + 1980' FWH of Sec 26, T-17S, R-32E Lea Co., N.M.	10. FIELD AND POOL, OR WILDCAT MCA Brachy SA Res.
14. PERMIT NO.	15. ELEVATIONS (Show whether FT, RT, CR, etc.) 3979' DF
	11. SEC., T., R., M., OR BLM. AND SURVEY OR AREA Sec. 26, T-17S, R-32E
	12. COUNTY OR PARISH Lea
	13. STATE N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

☐
☐
☐
☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

(Note: Report results of multiple completion or Well Completion or Recompletion Report and Log form.)

☐
☐
☐
☐

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(Other)

X

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Ran 586' of 4" 00, 11.34th FG Hydril Lines. Set shoe at 3900' & line hanger at 3297' w/pkr. Cont w/50 st class "c" cmt, w.o.c. 36 hrs. Ran 3 1/4" bit w/25th 2 3/8" FG DP on 2 3/8" tbg. Dild out plug at 3853'. Dild cmt from 3853' to 3903'. Cleaned out sand from 3903'-4007'. Ran 4" Baker model AD-I tension packer on 111th 2 3/8" cmt lined tbg set pkr at 3820'. Placed well on injection.

18. I hereby certify that the foregoing is true and correct

SIGNED

M. E. Spall

TITLE

Administrative Asst.

DATE

1-13-71

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD

JAN 15 1971

*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

USGS (5) file

MCA (3)

RECEIVED

JAN 1, 1971

U.S. CONSERVATION COMMISSION
WASHINGTON, D.C.