

Form 9-331
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on reverse side)Form approved,
Revised Bureau No. 42-11121

5. LEASE DESIGNATION AND SERIAL NO.

LC 057210

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT--" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ <i>Water inj. well</i>	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR	8. FARM OR LEASE NAME
Continental Oil Company	M.C.A. UNIT
3. ADDRESS OF OPERATOR	9. WELL NO.
P. O. Box 460, Hobbs, New Mexico 88240	184
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface	10. FIELD AND POOL, OR WILDCAT
1980' FWL + 1980' FWL of Sec 27, T-17S, R-32E, Lea County, N. Mex.	11. SEC., T., R., M., OR LMG. AND SURVEY OR AREA
14. PERMIT NO.	12. COUNTY OR PARISH
15. ELEVATIONS (Show whether DF, RT, CR, etc.)	13. STATE
3958'	LEA N. MEX.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) *Converted to water inj.*

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

This well was converted to water injection by the following procedures. Verbal approval to convert this well was given by Mrs. Gordon on 2-17-69.

Commenced cleanout work and found hole in casing. Cemented annulus from 1,050' to surface with 200 sacks of class C cement. Drilled out cement, cleaned out from 4038' to 4050' and drilled new 4 3/4" hole from 4050' to 4180'. Ran GR/N log. Ran 2 3/8" cement lined tubing with packer and tailpipe. Set packer at 3491' with tailpipe to 4135'. Placed well on injection 1-12-70.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Adm. Section Chief

DATE 1-13-70

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

USGS-5 FILE

ACCEPTED FOR RECORD

DATE

JAN 15 1970

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

*See Instructions on Reverse Side