

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-RU424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT-" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ <u>Water Injection Well</u>	5. LEASE DESIGNATION AND SERIAL NO. <u>LC 057210</u>
2. NAME OF OPERATOR <u>Continental Oil Company</u>	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR <u>P. O. Box 460, Hobbs, New Mexico 88240</u>	7. UNIT AGREEMENT NAME <u>MCA</u>
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) <u>At surface</u> <u>1980' FNL + 1980' FWL Sec. 27, T-17S, R-32E,</u> <u>in Lea County, N. Mex.</u>	8. FARM OR LEASE NAME <u>MCA Unit</u>
14. PERMIT NO.	9. WELL NO. <u>147</u>
15. ELEVATIONS (Show whether DF, ET, CR, etc.) <u>3996' DF</u>	10. FIELD AND POOL, OR WILDCAT <u>Maljamar G-5A Reservoir</u>
	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA <u>Sec. 27, T-17S, R-32E</u>
	12. COUNTY OR PARISH <u>Lea</u>
	13. STATE <u>N. Mex.</u>

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Convert to water injection

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

This well was converted to water injection by the following procedure. Verbal approval was given by Mr. Jordan on 2-17-69.

Found casing leak and replaced 107' of 5 1/2" casing at surface. Cleaned out fill from 3885' to 4037. Drilled cement from 4037' to 4100'. Drilled new hole to 4100'. Ran 2 3/8" cement lined tubing with packer and 660' of fiberglass tail pipe. Set packer at 3500' and placed well on injection. Injected 1285 BW with zero press in 24 hrs. on 10-7-69.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Adm. Section ChiefDATE 10-7-69

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED

USGS-5 FILE

OCT 13 1969

*See Instructions on Reverse Side

J. L. GORDON
ACTING DISTRICT ENGINEER

MCA Partners